

Publication

EP 0647736 A3 19950517

Application

EP 94113610 A 19940831

Priority

DE 4329741 A 19930903

Abstract (en)

[origin: US5534098A] A process for printing for producing a transparent imprint on a transparent fabric, comprises the steps of applying the ply of the fabric to be printed on onto a base provided with a heat-resistant anti-adhesive coating, feeding an offset-transfer onto the area of the fabric to be printed on, covering the areas of the fabric not to be printed on with a thermal insulation layer, applying pressure directed against the base at least on the offset-transfer at a temperature of more than 90 DEG C. for a period of at least 5 seconds, relieving at least the printed area of the fabric and removing the offset-transfer as well as the thermal insulation layer from the fabric and removing the fabric from the base.

IPC 1-7

B44C 1/17; **B41M 1/26**; **D06P 5/00**

IPC 8 full level

B41F 16/02 (2006.01); **B41M 1/26** (2006.01); **B41M 5/035** (2006.01); **B44C 1/17** (2006.01); **D06P 5/00** (2006.01); **D06P 5/24** (2006.01)

CPC (source: EP US)

B41F 16/02 (2013.01 - EP US); **B41M 5/0358** (2013.01 - EP US); **D06P 5/003** (2013.01 - EP US)

Citation (search report)

- [A] DE 2620512 A1 19771110 - HUDSON TEXTILWERKE GMBH
- [A] US 3788106 A 19740129 - TRUE H
- [A] CHEMICAL ABSTRACTS, vol. 93, no. 2, 14 July 1980, Columbus, Ohio, US; abstract no. 939506, KOBAYASHI: "Printing of textiles by the Yuzen printing method" page 73; & JP H0836363 A 19960206 - SHINETSU POLYMER CO

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

US 5534098 A 19960709; AT E164352 T1 19980415; DE 4329741 A1 19950309; DE 4329741 C2 19970206; DE 59405515 D1 19980430; EP 0647736 A2 19950412; EP 0647736 A3 19950517; EP 0647736 B1 19980325

DOCDB simple family (application)

US 30048194 A 19940902; AT 94113610 T 19940831; DE 4329741 A 19930903; DE 59405515 T 19940831; EP 94113610 A 19940831