

Title (en)

POSITIONING PROBE FOR A DRILL JIG IN KNEE SURGERY.

Title (de)

POSITIONIERUNGSSONDE FÜR EINE BOHRLEHRE BEI KNIEOPERATIONEN.

Title (fr)

SONDE DE POSITIONNEMENT POUR UN GABARIT DE PER AGE UTILISE EN CHIRURGIE DU GENOU.

Publication

**EP 0648095 A1 19950419 (EN)**

Application

**EP 93913389 A 19930617**

Priority

- GB 9301288 W 19930617
- GB 9213008 A 19920619

Abstract (en)

[origin: WO9400058A1] An anterior cruciate ligament (ACL) drill jig probe comprises a location portion (10) for securing in an ACL drill jig, a shank (11) extending from the location portion for passing one side of the patella tendon, and a horn (12) extending from a junction (13) with the shank (11) at an obtuse angle (OE) for location against the posterior part of the intercondylar notch as the anatomical reference point for an ACL drill jig with which the probe is to be used. The shank (11) has two lateral bends (16, 17) in opposite directions, both to facilitate passing of the shank round the lateral aspect of the medial femoral condyle and the patella tendon and to allow ready use of the probe with an existing coplanar ACL drill jig. A set of instruments comprises at least two interchangeable probes, one for a left knee and one for a right knee, with opposite handed bends (16, 17), and a coplanar ACL drill jig.

IPC 1-7

**A61B 17/16**

IPC 8 full level

**A61B 17/16** (2006.01); **A61B 17/17** (2006.01)

CPC (source: EP)

**A61B 17/1714** (2013.01); **A61B 17/1764** (2013.01)

Citation (search report)

See references of WO 9400058A1

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

**WO 9400058 A1 19940106**; EP 0648095 A1 19950419; GB 2268688 A 19940119; GB 2268688 B 19960605; GB 9213008 D0 19920805; GB 9312484 D0 19930804; JP H08500993 A 19960206

DOCDB simple family (application)

**GB 9301288 W 19930617**; EP 93913389 A 19930617; GB 9213008 A 19920619; GB 9312484 A 19930617; JP 50213394 A 19930617