

Title (en)

SURGE ARRESTOR FAIL SAFE THERMAL OVERLOAD MECHANISM.

Title (de)

EIGENSICHERER THERMISCHER ÜBERLASTMECHANISMUS FÜR ÜBERSPANNUNGSABLEITER.

Title (fr)

MECANISME DE SURCHARGE THERMIQUE A SECURITE INTEGREE POUR LIMITATEUR DE TENSION.

Publication

**EP 0648372 A1 19950419 (EN)**

Application

**EP 93918148 A 19930629**

Priority

- US 9306361 W 19930629
- US 90695292 A 19920630

Abstract (en)

[origin: WO9400864A1] A spring member (32) and associated channel member (28) bias a solder billet (22) into engagement with a ground electrode (16) of the surge arrestor. When the solder melts in response to a thermal overload condition the channel member (28) causes molten solder from the billet to flow preferentially along a path establishing a low resistance short circuit between the electrodes. Flow of the solder to desired locations is enhanced by solder flux, which preferably is of rosin type having substantial dielectric properties.

IPC 1-7

**H01H 39/00; H02H 3/22; H02H 7/24; H01T 1/14**

IPC 8 full level

**H02H 7/00** (2006.01); **H01R 4/24** (2006.01); **H01R 13/52** (2006.01); **H01T 1/14** (2006.01); **H04M 3/18** (2006.01); **H04Q 1/02** (2006.01)

CPC (source: EP KR)

**H01H 39/00** (2013.01 - KR); **H01R 4/2433** (2013.01 - EP); **H01R 13/5216** (2013.01 - EP); **H01T 1/14** (2013.01 - EP); **H04M 3/18** (2013.01 - EP); **H04Q 1/028** (2013.01 - EP)

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI NL PT SE

DOCDB simple family (publication)

**WO 9400864 A1 19940106**; AU 4770293 A 19940124; BR 9306641 A 19981208; CA 2139327 A1 19940106; CN 1082256 A 19940216; EP 0648372 A1 19950419; EP 0648372 A4 19950202; JP H07508397 A 19950914; KR 950702334 A 19950619; MX 9303916 A 19940429

DOCDB simple family (application)

**US 9306361 W 19930629**; AU 4770293 A 19930629; BR 9306641 A 19930629; CA 2139327 A 19930629; CN 93107663 A 19930630; EP 93918148 A 19930629; JP 50267094 A 19930629; KR 19940704806 A 19941229; MX 9303916 A 19930629