

Title (en)

Method for preventing weaving bar in a loom

Title (de)

Verfahren zur Vermeidung von Anlassstellen im Gewebe in einer Webmaschine

Title (fr)

Procédé pour éviter les bandes de tissage sur un métier à tisser

Publication

EP 0648875 B1 19991222 (DE)

Application

EP 93810723 A 19931014

Priority

EP 93810723 A 19931014

Abstract (en)

[origin: EP0648875A1] In the control method, the desired beat-up distance is varied with the effect of a lengthening or shortening, in order to avoid start-up points, for example thick and/or thin places, so that fabric, for example terry or plain fabric, with a programmed weft density is produced.
<IMAGE>

IPC 1-7

D03D 1/00; **D03D 49/60**; **D03D 39/22**

IPC 8 full level

D03D 1/00 (2006.01); **D03D 39/22** (2006.01); **D03D 49/60** (2006.01); **D03D 51/00** (2006.01)

CPC (source: EP US)

D03D 39/226 (2013.01 - EP US); **D03D 49/60** (2013.01 - EP US); **D03D 51/002** (2013.01 - EP US)

Cited by

EP0878571A1; CZ302560B6; CN103388226A

Designated contracting state (EPC)

BE DE IT

DOCDB simple family (publication)

EP 0648875 A1 19950419; **EP 0648875 B1 19991222**; DE 59309910 D1 20000127; JP 3515184 B2 20040405; JP H07173743 A 19950711; US 5499662 A 19960319

DOCDB simple family (application)

EP 93810723 A 19931014; DE 59309910 T 19931014; JP 23562994 A 19940929; US 32200094 A 19941012