

Title (en)

Device for controlling an unevenness of a sliver in a spinning machine.

Title (de)

Vorrichtung zur Vergleichsmässigung eines Faserbandes bei einer Spinnmaschine.

Title (fr)

Dispositif pour régulariser la section d'un ruban de fibres sur une machine de filature.

Publication

**EP 0649923 A1 19950426 (EN)**

Application

**EP 94810612 A 19941024**

Priority

JP 29013993 A 19931025

Abstract (en)

An electrostatic type detector 10 as a short cycle unevenness sensor is arranged upstream from a set of back rollers, while a long cycle unevenness sensor is arranged downstream from a set of front rollers. The detector 10 is arranged in a high frequency bridge circuit 25, which issues a signal indicating the short cycle unevenness of a sliver. A correction feedback circuit 28 is provided for directing the output signal to a variable capacitor 23 in the bridge circuit 25. An integrator 30 is provided in the correction feedback circuit 28 to obtain an average signal from the sliver unevenness detected by the detector 10, which average signal is used for varying the capacitance value of the variable capacitor 23. Such a correction feedback circuit allows the center of the operating range of the bridge circuit to be centered on the linear portion of the output characteristic of the bridge circuit. Furthermore, the value of the time constant of the integrator 30, in relation to the short cycle unevenness, is set to eliminate a low frequency components caused by long cycle unevenness as well as by temperature drift. As a result, only a component originating from the short cycle unevenness sensor is combined with a long cycle unevenness signal from the long cycle unevenness sensor to provide a signal for controlling the drafting ratio of the back and front rollers, whereby an unevenness of the sliver can be effectively reduced. <IMAGE>

IPC 1-7

**D01H 5/38**

IPC 8 full level

**D01H 5/42** (2006.01); **D01H 5/38** (2006.01); **D01H 13/22** (2006.01)

CPC (source: EP)

**D01H 5/38** (2013.01)

Citation (search report)

[A] PATENT ABSTRACTS OF JAPAN vol. 9, no. 45 (C - 268)<1768> 26 February 1985 (1985-02-26)

Cited by

GB2344111A; GB2344111B; US6679043B2; WO2004018748A1; US6223609B1

Designated contracting state (EPC)

CH DE IT LI

DOCDB simple family (publication)

**EP 0649923 A1 19950426**; **EP 0649923 B1 19970528**; DE 69403423 D1 19970703; DE 69403423 T2 19970925; JP 3271397 B2 20020402; JP H07118940 A 19950509

DOCDB simple family (application)

**EP 94810612 A 19941024**; DE 69403423 T 19941024; JP 29013993 A 19931025