

Title (en)

Snap-on cap for a beer keg.

Title (de)

Schnappverschluss für Bierfass.

Title (fr)

Fermeture erciquetable pour un fût à bière.

Publication

EP 0652160 A1 19950510 (EN)

Application

EP 94308002 A 19941031

Priority

GB 9322909 A 19931106

Abstract (en)

The cap can be push-fitted, for example, on a keg spear and has teeth 13 which engage over an annular projection 50 on the spear. The teeth are designed to permit easy fitting, but difficult removal. Each tooth 13 is hinged at 41 to the cap skirt, so as to move pivotally to permit passage over projection, but is biased to a position resisting removal. Each tooth is pivotally in the reverse direction when an attempt is made to remove the cap, causing a tail member (45) associated with the tooth to engage a stop (39) and serve as a resistive support for the tooth. <IMAGE>

IPC 1-7

B65D 41/48

IPC 8 full level

B65D 41/48 (2006.01); **B65D 55/08** (2006.01)

CPC (source: EP)

B65D 41/48 (2013.01); **B65D 55/0863** (2013.01)

Citation (search report)

- [XA] DE 4201997 C1 19921210
- [A] US 4796771 A 19890110 - STETTLER FRIEDRICH [CH]
- [DA] US 4779750 A 19881025 - ARMSTRONG KENNETH J [AU]
- [A] DE 9109221 U1 19910919

Cited by

EP1714899A1; EP0761556A1; EP1541483A1; FR2863257A1; NL1012741C2; CH690327A5; WO2004094237A3; WO9738913A1; WO0108991A1; EP4108593A1; BE1029529B1

Designated contracting state (EPC)

AT BE DE ES FR GB IE IT NL

DOCDB simple family (publication)

EP 0652160 A1 19950510; GB 9322909 D0 19931222

DOCDB simple family (application)

EP 94308002 A 19941031; GB 9322909 A 19931106