

Title (en)
Lock

Title (de)
Schloss

Title (fr)
Serrure

Publication
EP 0653535 B1 19970326 (DE)

Application
EP 93810792 A 19931115

Priority
EP 93810792 A 19931115

Abstract (en)
[origin: EP0653535A1] The multi-bolt lock has a latch (3) and a bolt (4) actuatable by a driver (16) on the lock cylinder (17). The lock has first transmission means (23, 25) connected operatively to the bolt (4) and detente means (28) for locking the latch (3), with the bolt moved out, and thus providing additional security. In the preferred version, the lock has a coupling member (33) which acts on a slide (8) attached to the latch shank (9), and, when the lock is screwed together ready, action can be taken on this coupling member from outside through an orifice in the lock case, in order to pull out the latch (3) together with the shank (9) and reverse it through 180 DEG , in such a way that the lock can be used both for left-closing and for right-closing doors. Such a lock affords increased security and allows efficient production and installation. <IMAGE>

IPC 1-7
E05C 9/02; E05B 59/00; E05B 13/00; E05B 63/04; E05B 55/06

IPC 8 full level
E05B 55/06 (2006.01); **E05B 59/00** (2006.01); **E05B 63/04** (2006.01); **E05C 9/02** (2006.01)

CPC (source: EP)
E05B 55/06 (2013.01); **E05B 59/00** (2013.01); **E05B 63/044** (2013.01); **E05C 9/026** (2013.01)

Cited by
CN109113451A; DE202008000676U1; DE10243890B3; EP0943765A1; CN110080627A; CN108699861A; ITUB20161254A1; EP1683936A1; EP1992772A1; CH694946A5; CN110805363A; EP2072726A3; DE202007017644U1; WO2017149028A1; WO2007006852A1

Designated contracting state (EPC)
AT CH DE LI NL

DOCDB simple family (publication)
EP 0653535 A1 19950517; **EP 0653535 B1 19970326**; AT E150834 T1 19970415; DE 59305974 D1 19970430

DOCDB simple family (application)
EP 93810792 A 19931115; AT 93810792 T 19931115; DE 59305974 T 19931115