

Title (en)
Printer

Title (de)
Drucker

Title (fr)
Imprimante

Publication
EP 0659574 B1 19990512 (EN)

Application
EP 94309820 A 19941223

Priority
JP 33358793 A 19931227

Abstract (en)

[origin: EP0659574A2] In a line printer, a rotation shaft (9) of a platen (2) is utilized as a fulcrum of a head-up lever (4). The head-up lever (4) and a bearing of the platen (2) are made in an integral form. As a result, the total number of parts of the line printer can be reduced and total number of assembling steps can also be reduced. Positioning of a print head (3) with respect to the platen (2) is achieved by establishing a precise engagement between a first pin (20) integrally formed on the edge portion of the print head (3) and a first guide groove (18) formed on a side wall (7,8) of a frame. As a consequence, the correct positioning of the print head can be performed with respect to the platen (2). On the other hand, a second pin (21) of the print head is journaled under a floating condition by a second guide groove (19) of the side (7,8) wall of the frame (1). This second pin (21) functions as a free fulcrum when the pressure contact of the print head (3) is released. As described above, play is formed at the free fulcrum of the head-up lever, so that distortion of parts and machining tolerance can be accommodated. Since the energizing force given to the print head (3) is performed by employing only one elastic member (14) around a centre of the platen (2) in the lengthwise direction, a so-called floating effect may be produced and eccentric abutting of the print head (3) and platen (2) can be avoided. The print head (3) is detachably assembled to the frame (1). The assembled print head (3) is held by a rear plate (12) which is similarly detachably engaged with the frame (1). The elastic member (14) is integrally assembled into the print head (2) together with the lock lever (17). As a result, the print head (3) can be simply assembled and can be easily replaced. Since the lock lever (17) is provided in order that the rear plate (12) is not easily accidentally removed, it is more possible that the print head is prevented from being dismounted when this is not desired. <IMAGE>

IPC 1-7
B41J 25/304; B41J 11/20; B41J 25/316; B41J 2/155

IPC 8 full level
B41J 11/20 (2006.01); **B41J 25/304** (2006.01)

CPC (source: EP)
B41J 11/20 (2013.01); **B41J 25/304** (2013.01)

Cited by
WO9840221A1; FR2760684A1; WO9840642A1

Designated contracting state (EPC)
FR IT

DOCDB simple family (publication)
EP 0659574 A2 19950628; **EP 0659574 A3 19960403**; **EP 0659574 B1 19990512**; JP 2000289289 A 20001017

DOCDB simple family (application)
EP 94309820 A 19941223; JP 2000090865 A 20000329