

Title (en)
Lockable plug

Title (de)
Verriegelbarer Stopfen

Title (fr)
Bouchon ne pouvant être Ôté qu'à l'aide d'une clé

Publication
EP 0665172 B1 19971105 (FR)

Application
EP 95400026 A 19950105

Priority
FR 9400588 A 19940120

Abstract (en)
[origin: EP0665172A1] The stopper comprises a top (1) with a tapping (2). A cap (3) which rotates freely in one direction on the screw top has an opening (4) in its top (5). An elastic ring (6) which is housed in a groove in the internal lateral face of the cap mates with the lower edge (7) of the top so as to prevent the top from leaving the cap . The upper face of the top has a dihedral part (8) constituting a male part. The cap has an upper sleeve (9), having the same axis (XX') as the cap, whose two bosses (10) overhang the male part. The key for the removal of the stopper has a female part of complementary form to the dihedral part of the male top and indentations conjugate with the bosses.

IPC 1-7
B65D 55/02

IPC 8 full level
B65D 50/06 (2006.01); **B65D 55/02** (2006.01)

CPC (source: EP)
B65D 50/067 (2013.01)

Cited by
CN104773382A

Designated contracting state (EPC)
AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 0665172 A1 19950802; EP 0665172 B1 19971105; AT E159909 T1 19971115; DE 69500962 D1 19971211; DE 69500962 T2 19980416; DK 0665172 T3 19980518; ES 2110813 T3 19980216; FR 2715135 A1 19950721; FR 2715135 B1 19960216; SI 0665172 T1 19980430

DOCDB simple family (application)
EP 95400026 A 19950105; AT 95400026 T 19950105; DE 69500962 T 19950105; DK 95400026 T 19950105; ES 95400026 T 19950105; FR 9400588 A 19940120; SI 9530045 T 19950105