

Title (en)

Method of manufacture a relay with movable slider

Title (de)

Verfahren zur Herstellung eines Relais mit beweglichem Schieber

Title (fr)

Procédé de fabrication d un relais à coulisseau mobile

Publication

EP 0669632 B1 20000503 (DE)

Application

EP 95101435 A 19950202

Priority

DE 4405222 A 19940218

Abstract (en)

[origin: US5572176A] An improved relay of conventional design is disclosed wherein the relay has an armature and at least one moveable contact element. A slide is attached to the armature and moveable contact element. The slide is of a length matched to the actual distance between the armature and the moveable contact element after the armature and moveable contact element are secured to a base and moved to a contact position.

IPC 1-7

H01H 50/64; **H01H 49/00**

IPC 8 full level

H01H 49/00 (2006.01); **H01H 50/64** (2006.01); **H01H 50/54** (2006.01)

CPC (source: EP US)

H01H 50/642 (2013.01 - EP US); **H01H 49/00** (2013.01 - EP US); **H01H 50/54** (2013.01 - EP US)

Cited by

WO2009141315A1

Designated contracting state (EPC)

AT CH DE FR GB IT LI

DOCDB simple family (publication)

US 5572176 A 19961105; AT E192604 T1 20000515; CA 2142665 A1 19950819; DE 4405222 C1 19950511; DE 59508238 D1 20000608; EP 0669632 A2 19950830; EP 0669632 A3 19970924; EP 0669632 B1 20000503

DOCDB simple family (application)

US 38569495 A 19950208; AT 95101435 T 19950202; CA 2142665 A 19950216; DE 4405222 A 19940218; DE 59508238 T 19950202; EP 95101435 A 19950202