

Title (en)

Fitting for a window or a door

Title (de)

Beschlag für ein Fenster oder eine Türe

Title (fr)

Ferrure pour une fenêtre ou une porte

Publication

EP 0671530 B2 20030423 (DE)

Application

EP 95102021 A 19950214

Priority

DE 9403801 U 19940307

Abstract (en)

[origin: EP0671530A1] The fitting comprises axially aligned driving bars (1,2) moved in opposite directions by a drive mechanism (3) between them and coupled to them by rails (15,16). A reversing rail (17) extends over these rails at their ends towards the mechanism, and prevents uncoupling of the bars from the actuating links (6,7). The reversing rail ends can be preloaded towards the opposite ends of the driving rails (15,16), being typically cranked or arched. It can be clipped onto the drive mechanism or have a bayonet-coupling to the latter, which can have a protruding pin with two opposite arms, passing through a mating hole in the rail and turned to lock the latter.

IPC 1-7

E05C 9/00

IPC 8 full level

E05C 9/00 (2006.01); **E05C 9/04** (2006.01); **E05C 9/20** (2006.01)

CPC (source: EP)

E05C 9/004 (2013.01); **E05C 9/041** (2013.01); **E05C 9/20** (2013.01)

Cited by

EP0960997A3; FR2953244A1; EP1881140A1

Designated contracting state (EPC)

DE GB IT

DOCDB simple family (publication)

DE 9403801 U1 19950406; DE 59503477 D1 19981015; EP 0671530 A1 19950913; EP 0671530 B1 19980909; EP 0671530 B2 20030423

DOCDB simple family (application)

DE 9403801 U 19940307; DE 59503477 T 19950214; EP 95102021 A 19950214