

Title (en)
Trough lock profile

Title (de)
Durchgehende Schliessleiste

Title (fr)
Profil de verrouillage traversant

Publication
EP 0672807 B1 19980422 (DE)

Application
EP 95100355 A 19950112

Priority
DE 9404559 U 19940318

Abstract (en)
[origin: EP0672807A1] The continuous closure strip (1) has a frame rail (2) with an outer surface (3) for the location of a seal of a door panel and at least one opening for a closure bolt of the lock of a door panel. The closure strip comprises only one arm and on the rear side (6) has at least one longitudinally extending rib (7) for engaging behind a corresp. projection (8) of the frame rail. The width dim. of the closure strip is so chosen that the strip in the installed position extends over the outer surface of the frame rail. The closure strip as far as the openings for fixture screws and the closure bolt of the door has a smooth and even outside (9) and on the opposite rear side (6) to this outside has at least one smooth locating surface (10) running parallel to the outside.

IPC 1-7
E05B 15/02; **E06B 5/10**; **E06B 1/52**

IPC 8 full level
E05B 15/02 (2006.01); **E05C 9/18** (2006.01); **E06B 1/52** (2006.01); **E06B 3/36** (2006.01); **E06B 3/88** (2006.01); **E06B 5/10** (2006.01); **E06B 5/11** (2006.01)

CPC (source: EP)
E05B 15/0205 (2013.01); **E05C 9/1808** (2013.01); **E06B 3/362** (2013.01); **E06B 3/88** (2013.01); **E06B 5/113** (2013.01)

Cited by
EP0829608A3; AT501601B1; EP0829603A3

Designated contracting state (EPC)
AT CH DE DK FR IT LI NL

DOCDB simple family (publication)
DE 9404559 U1 19940519; AT E165418 T1 19980515; DE 59501957 D1 19980528; EP 0672807 A1 19950920; EP 0672807 B1 19980422; EP 0807731 A2 19971119; EP 0807731 A3 19980408

DOCDB simple family (application)
DE 9404559 U 19940318; AT 95100355 T 19950112; DE 59501957 T 19950112; EP 95100355 A 19950112; EP 97109551 A 19950112