

Title (en)

Method and means for removing hickies from the printing plate in a printing machine

Title (de)

Verfahren und Vorrichtung zur Beseitigung von Butzen auf der Druckplatte einer Druckmaschine

Title (fr)

Procédé et dispositif pour enlever des mouches de la plaque d'impression d'une machine à imprimer

Publication

**EP 0673770 B1 19970416 (DE)**

Application

**EP 95103230 A 19950307**

Priority

DE 4410161 A 19940324

Abstract (en)

[origin: EP0673770A1] The rotational speed of the driven dipping roller (4) supplying humidity is altered by reducing the peripheral speed of the humidity-applicator roller (3). This ensures that the supply of humidifier to the humidity applicator roller is reduced. When the peripheral speed of the humidity applicator roller is again matched with that of the printing plate (7), the rotational speed of the roller supplying the humidifier reverts to its previous amount. The supply of humidifier is reduced by reducing the rotational speed of the roller (4).

IPC 1-7

**B41F 35/02**

IPC 8 full level

**B41F 35/02** (2006.01)

CPC (source: EP)

**B41F 35/02** (2013.01)

Cited by

EP0839652A3

Designated contracting state (EPC)

AT CH DE FR GB IT LI

DOCDB simple family (publication)

**EP 0673770 A1 19950927; EP 0673770 B1 19970416**; AT E151696 T1 19970515; DE 4410161 A1 19951005; DE 4410161 C2 19980226; DE 59500182 D1 19970522

DOCDB simple family (application)

**EP 95103230 A 19950307**; AT 95103230 T 19950307; DE 4410161 A 19940324; DE 59500182 T 19950307