

Title (en)  
Stroke adjusting device for presses or punching machines

Title (de)  
Hubverstelleinrichtung für Exzenterpressen oder Stanzen

Title (fr)  
Dispositif de réglage de la course pour presses ou poinçonneuses

Publication  
**EP 0676278 B1 19990303 (DE)**

Application  
**EP 95104720 A 19950330**

Priority  
DE 4412198 A 19940408

Abstract (en)  
[origin: EP0676278A1] The toothed section of the sliding socket (5) is continuous. For uncoupling, the socket is moved in direction towards the eccentric sleeve (6). When uncoupled, a locking unit (17) on the sliding socket is in connection with a holder (18) on the connecting rod (7), so that the eccentric sleeve is held non-turnable relative to the connecting rod. The locking unit consists of a projection, and the holder consists of a recess, to accommodate it when the socket is in uncoupled position. The socket has an untoothed guide section (19) and the driver ring (13) has guide section (20).

IPC 1-7  
**B30B 1/26**

IPC 8 full level  
**B30B 1/26** (2006.01)

CPC (source: EP)  
**B30B 1/263** (2013.01)

Cited by  
CN102562983A; CN104141755A

Designated contracting state (EPC)  
AT CH DE ES FR GB IT LI

DOCDB simple family (publication)  
**EP 0676278 A1 19951011; EP 0676278 B1 19990303**; AT E177052 T1 19990315; DE 4412198 C1 19950504; DE 59505156 D1 19990408; ES 2129690 T3 19990616

DOCDB simple family (application)  
**EP 95104720 A 19950330**; AT 95104720 T 19950330; DE 4412198 A 19940408; DE 59505156 T 19950330; ES 95104720 T 19950330