

Title (en)

Positioning device in a printing press.

Title (de)

Stellvorrichtung an einer Rotationsdruckmaschine.

Title (fr)

Dispositif de positionnement dans une presse à imprimer.

Publication

**EP 0679511 A3 19961127 (DE)**

Application

**EP 95104698 A 19950330**

Priority

DE 4414442 A 19940426

Abstract (en)

[origin: EP0679511A2] The adjustment device has an adjustment component rotatable about an axis between and positions. The adjustment component (4,12) and an indicator component (7,16) rotatably pivotable about an axis are connected together by a redn. gear which has a redn. factor transmitting the max. rotary angle of the rotatable adjustment component to at most a rotation of the indicator component. The redn. gear comprises a pinion (5,14) connected with the adjustment component and a toothed crown (6,15) driven by the pinion and connected to the indicator component. <IMAGE>

IPC 1-7

**B41F 13/14**

IPC 8 full level

**B41F 13/12** (2006.01); **B41F 13/14** (2006.01)

CPC (source: EP)

**B41F 13/14** (2013.01)

Citation (search report)

- [X] US 2860578 A 19581118 - TREGAY JOHN L
- [X] US 2989918 A 19610627 - POLGLASE JR BURTON C
- [A] DE 3023783 A1 19810326 - ADAMOVSKÉ STROJIRNÝ NP [CS]
- [A] EP 0401656 A2 19901212 - ROLAND MAN DRUCKMASCH [DE]

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

**EP 0679511 A2 19951102; EP 0679511 A3 19961127**; CA 2145442 A1 19951027; DE 4414442 A1 19951109; JP H07290683 A 19951107

DOCDB simple family (application)

**EP 95104698 A 19950330**; CA 2145442 A 19950324; DE 4414442 A 19940426; JP 9493195 A 19950420