

Title (en)

Method and device for treating textile products during drying.

Title (de)

Verfahren und Vorrichtung zur Behandlung von textilem Warengut während des Trocknungsprozesses.

Title (fr)

Procédé et dispositif pour le traitement de produits textiles pendant le séchage.

Publication

**EP 0679754 A3 19960117 (DE)**

Application

**EP 95105588 A 19950413**

Priority

DE 4414324 A 19940425

Abstract (en)

[origin: EP0679754A2] The chemical dry cleaning assembly, for clothing has a throttle (9) in the air recirculation system between the fan (7) and the cooling register (11). A gas measurement and control system (23) is connected to the temp. monitor (25) in the air flow (5) at the outlet side (3) of the drum (1), and to a pressure monitor (27), also with a link to the heating register (13). The heating register (13) is switched on and off according to the air flow (5) temp. and the throttle (9) is activated. A monitor (41) in the drum (1) gives a non-contact measurement of the temp. of the material being processed and is connected to the gas measurement and control (23) system. A controlled water contact unit (31) delivers water (45) to the drum (1) through a drying control (17) between the drum (1) and it. Also claimed is a control operation where the air flow vol. is constantly varied according to the concn. of solvent vapour in the air flow, taken at least from the temp. and pressure of the air flow at the outlet side of the drum. The temp. at the inlet side of the drum is lowered if the outlet temp. is higher than a set value. The temp. of the material being processed is measured without contact. When the material temp. rises, the heating register is disconnected and the cleaning process is stopped when the gas concn. in the air flow drops by more than a given value. Water pptd. from the air flow is caught before the cooling register, and returned to the processed material as a vapour in the drum when the air moisture content of the material drops below a certain value. The air moisture content is measured as well as the temp. and pressure. <IMAGE>

IPC 1-7

**D06F 43/08**

IPC 8 full level

**D06F 43/08** (2006.01); **D06F 58/28** (2006.01)

CPC (source: EP)

**D06F 43/086** (2013.01)

Citation (search report)

- [A] FR 2237151 A1 19750207 - REXROTH SZEKESSY ENTWICKLUNGS [DE]
- [A] DE 3215418 A1 19831027 - MIELE & CIE [DE]
- [A] US 4281465 A 19810804 - ZIMMERMANN MARTIN R, et al
- [X] PATENT ABSTRACTS OF JAPAN vol. 12, no. 390 (P - 772) 18 October 1988 (1988-10-18)
- [A] PATENT ABSTRACTS OF JAPAN vol. 17, no. 591 (C - 1125) 28 October 1993 (1993-10-28)

Cited by

EP0959173A1; US7018423B2; US6691536B2; DE102007042628A1; US6840963B2; US8549770B2; US6375686B1; WO0194686A3; US8661706B2; US8819958B2; US9580860B2; US6673764B2; US6855173B2; US6670317B2; US6828292B2; US7033985B2; US7063750B2; US6939837B2; EP1279760A2

Designated contracting state (EPC)

CH DE ES FR GR IT LI NL

DOCDB simple family (publication)

**DE 4414324 A1 19951026**; DE 59503660 D1 19981029; EP 0679754 A2 19951102; EP 0679754 A3 19960117; EP 0679754 B1 19980923; ES 2124929 T3 19990216

DOCDB simple family (application)

**DE 4414324 A 19940425**; DE 59503660 T 19950413; EP 95105588 A 19950413; ES 95105588 T 19950413