

Title (en)

Tooling for belt finishing of cylindrical bearings with diameter control of the bearings

Title (de)

Werkzeug zum Bandschleifen von zylindrischen Lagerflächen mit Durchmesserkontrolle der Lager

Title (fr)

Outils pour le toilage de portées cylindriques avec contrôle de diamètre des portées

Publication

EP 0680806 B1 19991027 (FR)

Application

EP 95400993 A 19950502

Priority

FR 9405449 A 19940504

Abstract (en)

[origin: EP0680806A1] The applicator, esp. for an abrasive strip used in machining cylindrical components such as crankshaft journals, consists of an arm which is able to pivot and move vertically, equipped with three shoes (7,8) - an upper central one (7) and two lower lateral ones (8a,8b) on jaws (2a,2b) which are pivoted to the arm and able to lock together so that the three shoes are located at the points of an equilateral triangle round the journal (6). The arm's first shoe has a concave surface for the abrasive strip, covering an angle of over 90 but less than 180 degrees, and is controlled by two horizontal sensors situated between the ends of the shoe and which measure the diameter of the journal. Each of the shoes on the two jaws also has a concave surface which extends through an angle of slightly less than 90 degrees, so that the three shoes together cover an angle of at least 270 degrees round the outer surface of the journal. <IMAGE>

IPC 1-7

B24B 5/42; **B24B 21/02**; **B24B 49/04**

IPC 8 full level

B24B 21/08 (2006.01); **B24B 5/42** (2006.01); **B24B 21/02** (2006.01); **B24B 49/04** (2006.01)

CPC (source: EP US)

B24B 5/42 (2013.01 - EP US); **B24B 21/02** (2013.01 - EP US); **B24B 49/04** (2013.01 - EP US)

Cited by

WO9743088A1

Designated contracting state (EPC)

DE ES GB IT

DOCDB simple family (publication)

EP 0680806 A1 19951108; **EP 0680806 B1 19991027**; DE 69512956 D1 19991202; DE 69512956 T2 20000621; ES 2138709 T3 20000116; FR 2719516 A1 19951110; FR 2719516 B1 19960726; JP H08150555 A 19960611; US 5651719 A 19970729

DOCDB simple family (application)

EP 95400993 A 19950502; DE 69512956 T 19950502; ES 95400993 T 19950502; FR 9405449 A 19940504; JP 10879795 A 19950502; US 43036595 A 19950428