

Title (en)

Device for the controlled operation of a gripper in a loom

Title (de)

Einrichtung zum gesteuerten Betätigen der Fadenklemme eines Greifers in Webmaschinen

Title (fr)

Dispositif pour l'actionnement contrôlé d'une griffe dans un métier à tisser

Publication

**EP 0681043 B1 19970730 (DE)**

Application

**EP 95105895 A 19950420**

Priority

DE 4415862 A 19940505

Abstract (en)

[origin: DE4415862C1] The object on which the invention is based is, in a device for the controlled actuation of the thread clamp of a gripper, to reduce the number of articulation points on the way from the control eccentric to the actuating element. A further object, in such a device, is to dispense largely or completely with spring elements which are necessarily present. According to the invention, this is achieved, on the one hand, in that a tracer roller 17, the free end of a link 13 carrying a control lever 10 and necessarily at least one spring element 20 engage at a common articulation point 14 of a roller lever 16 which transmits the curved movement of a single eccentric 18, and in that the link 13 is connected to the slay 1 by means of a rocker 24. The further object is achieved in that, in the device, an angle lever 16 equipped with tracer rollers 17, 29 is used instead of a spring-loaded one-armed roller lever 16 and a double eccentric 30, 31 is used instead of a single eccentric 18. <IMAGE>

IPC 1-7

**D03D 47/12**

IPC 8 full level

**D03D 47/00** (2006.01); **D03D 47/12** (2006.01); **D03D 47/18** (2006.01)

CPC (source: EP US)

**D03D 47/12** (2013.01 - EP US)

Designated contracting state (EPC)

BE CH DE FR GB IT LI

DOCDB simple family (publication)

**DE 4415862 C1 19950427**; DE 59500432 D1 19970904; EP 0681043 A1 19951108; EP 0681043 B1 19970730; JP 2682965 B2 19971126; JP H083840 A 19960109; US 5566725 A 19961022

DOCDB simple family (application)

**DE 4415862 A 19940505**; DE 59500432 T 19950420; EP 95105895 A 19950420; JP 10863995 A 19950502; US 42953795 A 19950426