

Title (en)

Device for pivoting a traversing flat can at a sliver delivering textile machine.

Title (de)

Vorrichtung zum Schwenken einer changierenden Flachkanne an einer Faserband abliefernden Textilmaschine.

Title (fr)

Dispositif pour pivoter un pot plat de va-et-vient d'une machine textile délivrant des mèches.

Publication

EP 0681980 A3 19970326 (DE)

Application

EP 95105556 A 19950412

Priority

- DE 4416948 A 19940513
- US 42656895 A 19950421

Abstract (en)

[origin: EP0681980A2] An appts. for swinging a traversing rectangular canister on a textile machine supplying sliver comprises a travelling traverse appts. with the canister held between its gripper plates which can swing across the traversing path. Here the swing appts. (15) is located on the canister (5) at a level in its upper region. Also claimed is an alternative swing appts. located on a level with the canister's lower region. PREFERRED - Pref. the means for moving the swing appts. are rollers (13, 14) located nearby on each side of the upper canister region, below a machine table (4) and facing opposite one another w.r.t. a rotating dish (2). They are both connected to the underside of the machine table by an eccentric axle which can be rotated by an adjustment lever connected to the piston rod of a cylinder in turn connected to a control appts. via conduits. <IMAGE>

IPC 1-7

B65H 54/78

IPC 8 full level

B65H 54/78 (2006.01); **B65H 67/04** (2006.01); **D01H 9/00** (2006.01)

CPC (source: EP US)

B65H 67/0428 (2013.01 - EP US); **B65H 2701/31** (2013.01 - EP US)

Citation (search report)

- [X] EP 0457099 A1 19911121 - RIETER AG MASCHF [CH]
- [XP] EP 0635448 A1 19950125 - RIETER INGOLSTADT SPINNEREI [DE]

Designated contracting state (EPC)

DE ES FR IT

DOCDB simple family (publication)

EP 0681980 A2 19951115; **EP 0681980 A3 19970326**; **EP 0681980 B1 19990728**; DE 4416948 A1 19951116; JP H08143224 A 19960604; US 5528797 A 19960625

DOCDB simple family (application)

EP 95105556 A 19950412; DE 4416948 A 19940513; JP 11169995 A 19950510; US 42656895 A 19950421