

Title (en)

Method and device in a paper machine or in a finishing device of same for collecting and removing of dust that is separated from the web.

Title (de)

Verfahren und Vorrichtung zum Sammeln und Entfernen von von einer Papierbahn abtrennendem Staub, für eine Papierherstellungs- oder Papierveredelungsmaschine.

Title (fr)

Méthode et dispositif pour l'enlèvement et la collection de poussière séparée d'une bande pour une machine à papier ou une machine de finition du papier.

Publication

EP 0682992 A3 19960501 (EN)

Application

EP 95850092 A 19950515

Priority

FI 942269 A 19940516

Abstract (en)

[origin: EP0682992A2] The invention concerns a method in a paper machine or in a finishing device of same, in particular in a slitter-winder, for collecting and removing of dust (D) and equivalent that are separated from the web (W), in which method a blowing (P1) is directed at the web (W), which separates dust (D) from the web (W), and in which method a suction effect (I1,I2) is applied to the web (W) so as to remove the separated dust (D) out of connection with the web (W). In the method, a high-pressure blowing (P1) is directed at the web (W) so as to separate the dust (D) from the web (W), and in the method, in the running direction (S) of the web (W), before and after said high-pressure blowing (P1), the dust and equivalent separated from the web (W) are sucked off. Further, the invention concerns a device in a paper machine or in a finishing device of same, in particular in a slitter-winder, for collecting and removing of dust (D) and equivalent that are separated from the web (W). The device (10) comprises a pressurized chamber space (11), in which there is a nozzle opening (12) for application of a blowing (P1) to the web (W) and a suction opening/openings (13,23) for removing the dust (D) present in connection with the web (W). The air chamber (11) in the device (10) is pressurized, a high-pressure blowing (P1) being fitted to be blown through the nozzle opening (12) of said air chamber (11) towards the web (W), and that the suction openings (13,23) of the device (10) are placed before and after said nozzle opening (12) in the running direction (S) of the web (W). <IMAGE>

IPC 1-7

B08B 5/02; **B08B 5/04**

IPC 8 full level

B01D 46/02 (2006.01); **B08B 5/02** (2006.01); **B08B 5/04** (2006.01)

CPC (source: EP)

B08B 5/02 (2013.01); **B08B 5/026** (2013.01); **B08B 5/046** (2013.01); **B08B 2205/005** (2013.01)

Citation (search report)

- [XA] FR 2306752 A1 19761105 - TURNER MACHINERY LTD [GB]
- [XA] DE 2602236 A1 19770728 - MASCHF AUGSBURG NUERNBERG AG
- [PX] EP 0640411 A1 19950301 - SHINKO KK [JP]
- [XA] EP 0084633 A2 19830803 - KELVA AB [SE]
- [XA] DE 2006716 A1 19700903
- [A] DE 1786277 A1 19720120 - GRUENENFELDER HANS
- [A] EP 0480631 A2 19920415 - MOORES J & C LTD [GB]

Cited by

CN103286099A; CN105964072A; US6148831A; CN114466707A; EP0870869A1; EP3885056A1; EP0810039A3; EP1787732A1; DE102005055312A1; US5800679A; EP2735381A1; CN103831274A; DE10016822A1; DE10016822C2; DE29618023U1; WO2021104732A1; WO9915731A1; US6511581B1; US6558456B2; WO9819009A1; WO9731151A1; US6680086B1; US6787196B2; US7198841B2; US11724289B2; KR100267630B1

Designated contracting state (EPC)

AT DE FR GB IT SE

DOCDB simple family (publication)

EP 0682992 A2 19951122; **EP 0682992 A3 19960501**; CA 2149344 A1 19951117; FI 942269 A0 19940516; FI 95611 B 19951115; FI 95611 C 19960226; JP H07323208 A 19951212

DOCDB simple family (application)

EP 95850092 A 19950515; CA 2149344 A 19950515; FI 942269 A 19940516; JP 14005995 A 19950516