

Title (en)

Upper tool and upper tool assembly comprising said upper tool for use with a press brake and method of clamping said upper tool

Title (de)

Oberwerkzeug und Oberwerkzeugträger mit einem solchen Oberwerkzeug zur Verwendung mit einer Biegepresse und Verfahren zur Befestigung des Oberwerkzeuges

Title (fr)

Outil supérieur et ensemble de support comportant un tel outil supérieur pour une presse plieuse et méthode de fixation de l'outil supérieur

Publication

EP 0682995 B1 20021030 (EN)

Application

EP 95401135 A 19950516

Priority

- JP 10270094 A 19940517
- JP 14978594 A 19940630
- JP 19543494 A 19940819

Abstract (en)

[origin: EP0682995A1] In an upper tool for a press brake clamped between a support plate (7) of an upper tool holder body (5) attached to a lower portion of an upper table (3) and an upper tool clamp member (11), the upper tool (9) is formed with an inclined surface (9S) narrowed upward at an upper portion thereof and with an engage groove (9G) engaged with an engage projection (11K) of the upper tool clamp member (11) and formed under the inclined surface (9S). Therefore, the inclined surface (9S) is brought into contact with an inclined surface of the upper tool clamp member (11), when the upper tool is clamped between the upper tool holder body (5) and the upper tool clamp member (11), in such a way that clamping force can be further increased when the upper tool is engaged with a die (63). Further, in an upper tool holder apparatus for a press brake, the pivotal upper tool clamp member (211) is formed with an engage projection (211P) engaged with a drop prevention groove (205G) formed in the upper tool (205), and the upper tool holder apparatus further comprises clamp operation lever (215) for selectively moved to a clamp position A at which the clamping force can be applied to the upper tool clamp member (211) from the clamping force generating spring (213) to clamp the upper tool tightly; an unclamp position B at which the clamping force can be reduced to allow the upper tool to be adjustably shifted horizontally, and an exchange position C at which the upper tool clamp member (211) can be moved way from the upper tool to allow the upper tool to be exchanged vertically with another one. <IMAGE>

IPC 1-7

B21D 5/02

IPC 8 full level

B21D 5/02 (2006.01)

CPC (source: EP KR)

B21D 5/02 (2013.01 - EP KR); **B21D 5/0209** (2013.01 - EP); **B21D 5/0236** (2013.01 - EP)

Cited by

ITMI20100110A1; CN105252681A; CN112680769A; EP3906126A4; CN113981182A; IT202000016165A1; NL1005108C2; CN105750409A; US7069766B2; WO02064278A1; WO2011092558A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0682995 A1 19951122; EP 0682995 B1 20021030; CN 1063989 C 20010404; CN 1125647 A 19960703; CN 2312084 Y 19990331; DE 69528684 D1 20021205; DE 69528684 T2 20030710; DE 69535526 D1 20070809; DE 69535526 T2 20080306; EP 1213062 A2 20020612; EP 1213062 A3 20050202; EP 1213062 B1 20070627; KR 100377710 B1 20030625; KR 950031491 A 19951218; MY 114880 A 20030228; SG 38842 A1 19970417; TW 365857 U 19990801

DOCDB simple family (application)

EP 95401135 A 19950516; CN 95106092 A 19950516; CN 96240427 U 19961217; DE 69528684 T 19950516; DE 69535526 T 19950516; EP 01123583 A 19950516; KR 19950012062 A 19950516; MY PI9501249 A 19950512; SG 1995000441 A 19950512; TW 84204933 U 19950417