

Title (en)

SAFETY DEVICE FOR LOCKING A STRIKER, AND METHODS FOR FABRICATING SUCH DEVICE

Title (de)

SCHLAGBOLZENSICHERUNG UND VERFAHREN ZU SEINER HERSTELLUNG

Title (fr)

DISPOSITIF DE SECURITE POUR VERROUILLER UN PERCUTEUR ET PROCEDE DE FABRICATION DE CE DISPOSITIF

Publication

**EP 0685059 B1 19980909 (FR)**

Application

**EP 95902158 A 19941122**

Priority

- FR 9401356 W 19941122
- FR 9315203 A 19931217

Abstract (en)

[origin: WO9516891A1] The invention relates to a safety device for locking a striker for a fuse of a rotational projectile. The device according to the invention comprises a spiral spring (12) consisting of an elastic tape wound on itself and loaded by its elasticity around a locking member which maintains the striker (2) in a safety position, the device of the invention being characterized in that the locking member is comprised of a flexible band (9) wound around the striker (2) and of which the material or the geometry are such that it does not exert any elastic return effort onto the striker (2), the band having a length such that, upon firing, when it is unwound after the spiral spring (12) and applied against the latter due to the centrifugal force, the ends (9a, 9b) of the band overlap. Application to medium calibre ammunition.

IPC 1-7

**F42C 15/22**

IPC 8 full level

**F42C 15/22** (2006.01)

CPC (source: EP US)

**F42C 15/22** (2013.01 - EP US)

Designated contracting state (EPC)

CH DE DK ES GB GR LI NL SE

DOCDB simple family (publication)

**WO 9516891 A1 19950622**; AU 1111495 A 19950703; AU 678654 B2 19970605; DE 69413207 D1 19981015; DE 69413207 T2 19990304; EP 0685059 A1 19951206; EP 0685059 B1 19980909; FR 2714169 A1 19950623; FR 2714169 B1 19960209; SG 54298 A1 19981116; TR 27938 A 19951026; US 5625161 A 19970429

DOCDB simple family (application)

**FR 9401356 W 19941122**; AU 1111495 A 19941122; DE 69413207 T 19941122; EP 95902158 A 19941122; FR 9315203 A 19931217; SG 1996007943 A 19941122; TR 128894 A 19941213; US 49187195 A 19950710