

Title (en)
Locking mechanism

Title (de)
Sperrvorrichtung

Title (fr)
Mécanisme de verrouillage

Publication
EP 0685191 B1 19980722 (FR)

Application
EP 95870045 A 19950503

Priority
BE 9400458 A 19940504

Abstract (en)
[origin: EP0685191A1] The clip (4) pivots (5) on the back of the seat frame (1), while its other end engages in notches (9,10) in the end of the back frame (3). A spring (7) moves the clip and lies between the end of the clip (6) and a point (8) on the seat frame. When the back frame is its horizontal position the clip engages in a recess (12), beyond the notches. The depth of the recess is sufficient to prevent any contact of the end of the clip with the edge (11) of the back frame. <IMAGE>

IPC 1-7
A47C 17/16; **A47C 20/04**

IPC 8 full level
A47C 17/16 (2006.01); **A47C 20/04** (2006.01)

CPC (source: EP)
A47C 1/026 (2013.01); **A47C 17/162** (2013.01); **A47C 20/045** (2013.01)

Cited by
BE1023810B1

Designated contracting state (EPC)
BE DE DK ES FR GB IT PT SE

DOCDB simple family (publication)
EP 0685191 A1 19951206; **EP 0685191 B1 19980722**; BE 1008239 A6 19960220; CN 1123642 A 19960605; CN 1124100 C 20031015; CN 1444890 A 20031001; CN 2246209 Y 19970129; DE 69503568 D1 19980827; DE 69503568 T2 19990121; DK 0685191 T3 19990426; ES 2119350 T3 19981001; SI 0685191 T1 19981031

DOCDB simple family (application)
EP 95870045 A 19950503; BE 9400458 A 19940504; CN 03106053 A 20030218; CN 95105436 A 19950428; CN 95211405 U 19950428; DE 69503568 T 19950503; DK 95870045 T 19950503; ES 95870045 T 19950503; SI 9530115 T 19950503