

## Title (en)

Process and use of an installation for the selective hydrogenation of catalytic cracking gasoline

## Title (de)

Verfahren und Verwendung einer Anlage für die selektive Hydrierung von katalytischen Crackbenzinen

## Title (fr)

Procédé et utilisation d'une installation pour le traitement par hydrogénation sélective d'une essence de craquage catalique

## Publication

**EP 0685552 B2 20021127 (FR)**

## Application

**EP 95401244 A 19950529**

## Priority

FR 9406708 A 19940601

## Abstract (en)

[origin: EP0685552A1] A new method is used for the selective hydrogenation of petrol, obt'd. from a catalytic cracking process, with a di-olefin content less than 5%, cyclopentadiene less than 1%, mercaptans 1-300 ppm. The petrol cut C5 - 210 degrees C is contacted with a catalyst comprising 0.1-1% Pd deposited on a support contg. at least 50% Al<sub>2</sub>O<sub>3</sub>, at 4-25 bar, 80-200 degrees C and LHSV of 1-10h<-1>. Figures (1) and (2) illustrate the nature of the process. In figure (1), a C3-180 degrees C cut is delivered to the de-butaniser (3) to separate the C3-C4 fraction. The C5-180 degrees C (or C5-160 degrees C or C5-210 degrees C, where applicable), i.e. the C5 + petrol cut from catalytic cracking is introduced in a zone (4) of selective hydrogenation and H<sub>2</sub> in also introduced (5). The hydrogenated cut passes into (6) of sepn. which is a de-pentaniser (C5 sepn.) or de-hexaniser (C5 + C6 sepn.). Thus a C5 or C5 + C6 fraction is obt'd., sent to an etherification unit and a C7+ fraction sent to a petrol stock. The catalytic hydrogenation reactor, shown in figure (2), (10) is arranged in two catalytic zones (11) and (12); the first is traversed by the liq. charge and some H<sub>2</sub> (less than the stoichiometric amt. necessary to convert all diolefins to mono olefins). In this zone the sweetening process also takes place. The second zone receives the charge from the first zone (and the remainder of the H<sub>2</sub> required to convert diolefin to olefins and to isomerise prim. and sec. olefins to tert olefins). The proportion (vol.) of the first zone is at most 50% of the sum of the two zones (pref. 15-30%). The hydrogenation unit operates at pressures lower than the de-butaniser, and the de-pentaniser (or de-hexaniser) requires only 13-15 bar. Charge circulation can thus be effected by a slight de-pressurisation at the exit of the hydrogenation unit. The high temp. at the base of the de-butaniser and the high activity of the hydrogenation catalyst allows the unit (4) to be operated without further pre-heating of the charge.

## IPC 1-7

**C10G 45/40**; **C10G 69/04**

## IPC 8 full level

**C10G 45/40** (2006.01); **C10G 69/04** (2006.01)

## CPC (source: EP)

**C10G 45/40** (2013.01); **C10G 69/04** (2013.01)

## Citation (opposition)

Opponent :

- US 5266188 A 19931130 - KUKES SIMON G [US], et al
- US 5254789 A 19931019 - GAJDA GREGORY J [US]
- US 3470085 A 19690930 - PARKER ROBIN J

## Cited by

US6118034A; CN104560135A; EP3317238A4; FR2764299A1; EP0884373A1; EP0832958A1; FR2753717A1; US6007704A; CN114763493A; EP0884102A1; FR2764210A1; EP0831140A1; FR2753718A1; WO2012022849A1; US6709639B1; US6838060B1; EP2161076A1; US6686309B1; US6187173B1

## Designated contracting state (EPC)

DE ES GB IT

## DOCDB simple family (publication)

**EP 0685552 A1 19951206**; **EP 0685552 B1 20000209**; **EP 0685552 B2 20021127**; DE 69514957 D1 20000316; DE 69514957 T2 20001012; DE 69514957 T3 20110818; ES 2144587 T3 20000616; ES 2144587 T5 20030616; FR 2720754 A1 19951208; FR 2720754 B1 19960726

## DOCDB simple family (application)

**EP 95401244 A 19950529**; DE 69514957 T 19950529; ES 95401244 T 19950529; FR 9406708 A 19940601