

Title (en)

Process for preventing handle hardening by printing and dyeing cellulosic textiles.

Title (de)

Verfahren zur Vermeidung der Griffverhärtung beim Bedrucken und Färben von cellulosehaltigen Textilien.

Title (fr)

Procédé pour éviter le durcissement du toucher lors de la teinture et l'impression de textiles cellulosiques.

Publication

EP 0685590 A2 19951206 (DE)

Application

EP 95108049 A 19950526

Priority

DE 4419533 A 19940603

Abstract (en)

Process for preventing cellulosic textiles developed a hard feel when dyed or printed comprises using a dye formulation based on reactive dye(s) with at least 2 reactive gps., which contains 0.5-10 wt.% surfactant and 0-10 wt.% antifoam(s) w.r.t. the dye(s). Also claimed are the reactive dye formulation per se; a printing paste contg. this formulation and an alginate thickener; and a method for making the paste.

Abstract (de)

Cellulosehaltige Textilien werden ohne Griffverhärtung mit Mehrfachanker-Reaktivfarbstoffen bedruckt oder gefärbt, indem man eine Reaktivfarbstoffpräparation verwendet, die 0,5 bis 10 Gew.-% eines Tensids und 0 bis 10 Gew.-% eines Entschäumungsmittels enthält.

IPC 1-7

D06P 3/60; **D06P 1/651**; **D06P 1/607**; **D06P 1/613**

IPC 8 full level

D06P 1/44 (2006.01); **D06P 1/48** (2006.01); **D06P 1/52** (2006.01); **D06P 1/607** (2006.01); **D06P 1/613** (2006.01); **D06P 1/649** (2006.01); **D06P 1/651** (2006.01); **D06P 1/667** (2006.01); **D06P 3/66** (2006.01)

CPC (source: EP US)

D06P 1/48 (2013.01 - EP US); **D06P 1/5292** (2013.01 - EP US); **D06P 1/607** (2013.01 - EP US); **D06P 1/6076** (2013.01 - EP US); **D06P 1/613** (2013.01 - EP US); **D06P 1/6136** (2013.01 - EP US); **D06P 1/6138** (2013.01 - EP US); **D06P 1/6495** (2013.01 - EP US); **D06P 1/65118** (2013.01 - EP US); **D06P 1/667** (2013.01 - EP US); **D06P 3/66** (2013.01 - EP US); **Y10S 8/904** (2013.01 - US); **Y10S 8/907** (2013.01 - US); **Y10S 8/912** (2013.01 - US); **Y10S 8/918** (2013.01 - US); **Y10S 8/921** (2013.01 - US)

Cited by

CN105544251A

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI PT

DOCDB simple family (publication)

EP 0685590 A2 19951206; **EP 0685590 A3 19980506**; BR 9502669 A 19960102; CA 2150852 A1 19951204; CN 1122854 A 19960522; DE 4419533 A1 19951207; JP H0849174 A 19960220; TR 28535 A 19961001; TW 338073 B 19980811; US 5634949 A 19970603

DOCDB simple family (application)

EP 95108049 A 19950526; BR 9502669 A 19950605; CA 2150852 A 19950602; CN 95106602 A 19950601; DE 4419533 A 19940603; JP 13699095 A 19950602; TR 65595 A 19950601; TW 84106207 A 19950616; US 46296495 A 19950605