

Title (en)
Switch for overhead conveyor system

Title (de)
Weiche für eine Hängefördereinrichtung

Title (fr)
Aiguillage pour convoyeur suspendu

Publication
EP 0686728 B1 19991222 (DE)

Application
EP 95108650 A 19950606

Priority
DE 9409156 U 19940606

Abstract (en)
[origin: EP0686728A1] The points switch comprises two tongues (11,12), coupled for simultaneous change over of the points. The tongues pivot at the ends of second rails (3,4), and are connected alternately via their free ends to the end of the first rail (2). Coupling is by a spring component (14) of variable length, and which exerts a predetermined force. The force can be such that the component acts as a rigid one under the forces occurring during changeover. It can act on the tongues near their pivot points (12,13), and typically between the latter and their free ends (11a,12a), containing a compression spring. <IMAGE>

IPC 1-7
E01B 25/26

IPC 8 full level
E01B 25/26 (2006.01)

CPC (source: EP)
E01B 25/26 (2013.01)

Designated contracting state (EPC)
DE FR IT

DOCDB simple family (publication)
DE 9409156 U1 19951012; DE 59507455 D1 20000127; EP 0686728 A1 19951213; EP 0686728 B1 19991222

DOCDB simple family (application)
DE 9409156 U 19940606; DE 59507455 T 19950606; EP 95108650 A 19950606