

Title (en)
Offset device for a strap belt

Title (de)
Versatzvorrichtung für ein Gurtband

Title (fr)
Dispositif de déport de sangle

Publication
EP 0687796 A1 19951220 (FR)

Application
EP 95401389 A 19950614

Priority
FR 9407388 A 19940616

Abstract (en)
The webbing guide comprises a base (1) with several legs (2), providing an opening (4) for the passage of a rotating bearing (5). The bearing has an opening (9) for mounting of a roller bearing (10) giving automatic positioning of the roller bearing relative to the webbing track. The orientation of the lateral faces of the legs is not parallel, extending in an L, T or H shape. The bearings are located on each face along the secant rotational axes. Radial stops are included in the bearings which limit the rotational amplitude between two angular positions. A roller bearing cage is interposed in the rolling zone between the bearing and the leg. A connecting pivot is between the bearing and the leg and is limited in amplitude by the stops. Guidance of the bearing in its housing is assured by a machined cage in a seat.

IPC 1-7
E06B 9/78

IPC 8 full level
E06B 9/78 (2006.01)

CPC (source: EP)
E06B 9/78 (2013.01); **E06B 2009/785** (2013.01)

Citation (search report)
• [A] FR 2624908 A1 19890623 - HEIMERDINGER MAURICE [FR]
• [A] DE 8610444 U1 19860528

Designated contracting state (EPC)
BE DE ES IT NL

DOCDB simple family (publication)
EP 0687796 A1 19951220; EP 0687796 B1 19980909; DE 687796 T1 19961010; DE 69504578 D1 19981015; DE 69504578 T2 19990204; ES 2081794 T1 19960316; ES 2081794 T3 19981101; FR 2721302 A1 19951222; FR 2721302 B1 19960906

DOCDB simple family (application)
EP 95401389 A 19950614; DE 69504578 T 19950614; DE 95401389 T 19950614; ES 95401389 T 19950614; FR 9407388 A 19940616