

Title (en)  
Open-head metal drum

Title (de)  
Deckelfass aus Metall

Title (fr)  
Fût métallique à ouverture totale

Publication  
**EP 0690001 B1 19961106 (FR)**

Application  
**EP 95870075 A 19950621**

Priority  
BE 9400608 A 19940627

Abstract (en)  
[origin: EP0690001A1] The barrel consists of a cylindrical body (1) and a circular lid (8), with a C-section locking ring (12) to hold the lid in place. The upper edge of the barrel has a flattened rim (3) made from a double fold (4,5), and below the rim the barrel wall has an annular recess (6). The lid has a peripheral channel (9) to receive the upper edge of the barrel body, the outer side of which is cylindrical in shape. The locking ring has upper (13) and lower (15) branches, the upper one fitting over the outer rim of the lid and the lower one engaging with the recess in the barrel wall. The inside of the barrel can be covered by a protective film layer in the form of a bag, the upper edge of which is held in place between the barrel rim and lid. <IMAGE>

IPC 1-7  
**B65D 8/04; B65D 45/30**

IPC 8 full level  
**B65D 8/02** (2006.01); **B65D 45/32** (2006.01)

CPC (source: EP)  
**B65D 7/045** (2013.01); **B65D 45/32** (2013.01); **B65D 2543/00972** (2013.01)

Designated contracting state (EPC)  
BE DE ES FR GB NL

DOCDB simple family (publication)  
**BE 1007765 A5 19951017**; DE 69500080 D1 19961212; DE 69500080 T2 19970430; EP 0690001 A1 19960103; EP 0690001 B1 19961106;  
ES 2094071 T3 19970101

DOCDB simple family (application)  
**BE 9400608 A 19940627**; DE 69500080 T 19950621; EP 95870075 A 19950621; ES 95870075 T 19950621