

Title (en)
Double barreled rifle

Title (de)
Zweiläufiges Gewehr

Title (fr)
Fusil à deux canons

Publication
EP 0690282 A3 19960911 (DE)

Application
EP 95109662 A 19950622

Priority
DE 4422905 A 19940630

Abstract (en)
[origin: EP0690282A2] The shoulder block (5) also encloses the second barrel (2) and is drilled out (7) round the barrel with clearance. The shoulder block is fitted out with adjusting screws (8,9) which are spaced out at 60 to 120 deg. round the second barrel so as to lie radially to the barrel axis (A2) with their inner ends against the barrel (2) casing. The two barrels (1,2) can move freely in relation to one another in an area ahead of the shoulder block (5), and also freely in relation to their axes (A1,A2). The two screws are offset by 90 deg. round the barrel rim and are set at angle (MU)= 45 deg. in relation to a centre plane drawn through the two axes (A1,A2). The screws are in turn diametrically opposed counter-screws (10,11) and the shoulder itself is enclosed by a removable front shaft at its forward end, using a shoulder block groove to lock the shaft into position.

IPC 1-7
F41A 21/08

IPC 8 full level
F41A 21/00 (2006.01); **F41A 21/08** (2006.01)

CPC (source: EP)
F41A 21/08 (2013.01)

Citation (search report)
• [AD] DE 3525535 A1 19870129 - BAIER OTTO
• [AD] DE 2843363 A1 19800424 - BLASER HORST
• [AD] DE 2816128 A1 19791018 - PACINER RUDOLF
• [A] AT 372520 B 19831025 - KNIPP HEINZ H F [DE]
• [A] DE 3834304 C1 19900208

Designated contracting state (EPC)
AT CH DE ES FR LI SE

DOCDB simple family (publication)
EP 0690282 A2 19960103; EP 0690282 A3 19960911; EP 0690282 B1 19980916; AT E171265 T1 19981015; CZ 172095 A3 19960117; CZ 285804 B6 19991117; DE 4422905 C1 19951221; DE 59503587 D1 19981022; ES 2123186 T3 19990101; FI 109053 B 20020515; FI 953168 A0 19950626; FI 953168 A 19951231

DOCDB simple family (application)
EP 95109662 A 19950622; AT 95109662 T 19950622; CZ 172095 A 19950629; DE 4422905 A 19940630; DE 59503587 T 19950622; ES 95109662 T 19950622; FI 953168 A 19950626