

Title (en)  
Operating handle

Title (de)  
Bedienungsgriff

Title (fr)  
Lever d'actionnement

Publication  
**EP 0692592 A1 19960117 (DE)**

Application  
**EP 95106089 A 19950424**

Priority  
DE 9411387 U 19940714

Abstract (en)  
The handle has a catch pin (7) which is mounted in a bushing (18) fitting into the hole (17) in the mandrel (5). The base (20) of the bushing is joined to the surface (21) of the mandrel. The catch head (16) has at least one flat part (24) formed by the surface (25) of the catch head. The cross-section of the opening (26) in the bushing base matches the cross-section of the catch-head. The other end of the bushing has a closure lid (19) and the mandrel has a protuberance. The mandrel cavity in the drive element has a matching longitudinal groove. The protuberance consists of a lug pressed out of the material of the mandrel. <IMAGE>

Abstract (de)  
Die Erfindung betrifft einen Bedienungsgriff mit einer am Dorn angeordneten Kupplung zur formschlüssigen Verbindung mit einem Antriebselement. Erfindungsgemäß wird vorgeschlagen, am freien Ende (6) des Dorns (5) einen verschieblichen Rastkopf (16) anzuordnen, der das Antriebselement (10) nach der Montage des Bedienungsgriffs (1) hintergreift. <IMAGE>

IPC 1-7  
**E05B 3/02**

IPC 8 full level  
**E05B 3/02** (2006.01); **E05B 3/08** (2006.01); **G05G 1/08** (2006.01)

CPC (source: EP)  
**E05B 3/08** (2013.01); **G05G 1/085** (2013.01)

Citation (search report)

- [Y] EP 0058391 A1 19820825 - WILKE RUDOLF
- [Y] EP 0193081 A2 19860903 - WILKE RUDOLF
- [A] DE 2324619 A1 19741205 - VOSS KG J
- [A] US 2191613 A 19400227 - ERICSSON ERIC W

Cited by  
EP1944442A1

Designated contracting state (EPC)  
AT DE FR IT

DOCDB simple family (publication)  
**EP 0692592 A1 19960117**; **EP 0692592 B1 19980916**; AT E171241 T1 19981015; DE 59503590 D1 19981022; DE 9411387 U1 19940908

DOCDB simple family (application)  
**EP 95106089 A 19950424**; AT 95106089 T 19950424; DE 59503590 T 19950424; DE 9411387 U 19940714