

Title (en)

A bidirectional load current sense circuit for a H-bridge

Title (de)

Bidirektionale Stromabfühlschaltung für eine H-Brücke

Title (fr)

Un circuit de détection du courant de charge bi-directionnel pour un pont de type-H

Publication

**EP 0693749 B1 20010523 (EN)**

Application

**EP 94410051 A 19940719**

Priority

EP 94410051 A 19940719

Abstract (en)

[origin: EP0693749A1] The present invention relates to a current sense device for a load arranged in a diagonal of a H-bridge comprising MOS transistors (M1, M2, M3, M4) and operating in class AB, characterized in that it comprises first means, independent from the H-bridge, for measuring the current (I) flowing in the load (1). A current-voltage converter (3) for converting the current measured by said first means into a voltage (Vout) proportional to said current, this voltage being applied to a sense amplifier that determines the transconductance gain of a control amplifier of the transistors of the H-bridge. <MATH>

IPC 1-7

**G11B 5/55**

IPC 8 full level

**G01R 17/16** (2006.01); **G11B 5/54** (2006.01); **G11B 5/55** (2006.01)

CPC (source: EP US)

**G11B 5/5526** (2013.01 - EP US)

Cited by

US6753717B2; EP0834871A1; US6151186A; US7616458B2; EP2515126A1; US8796998B2; US10516955B2; WO2012143590A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

**EP 0693749 A1 19960124**; **EP 0693749 B1 20010523**; DE 69427292 D1 20010628; JP 2996145 B2 19991227; JP H08105920 A 19960423; US 5644484 A 19970701

DOCDB simple family (application)

**EP 94410051 A 19940719**; DE 69427292 T 19940719; JP 20188395 A 19950717; US 50188195 A 19950713