

Title (en)  
Method of lining a blast furnace

Title (de)  
Verfahren zum Zustellen eines Hochofens

Title (fr)  
Procédé pour le garnissage d'un haut fourneau

Publication  
**EP 0694619 A2 19960131 (EN)**

Application  
**EP 95304388 A 19950622**

Priority  
US 28048894 A 19940726

Abstract (en)  
A method is provided for lining a blast furnace or other metallurgical vessel in stages using a plurality of porous consumable forms and a pumpable casting composition. A form member, including a rigid support frame and a porous consumable form mounted thereto, is installed in a lower portion of the vessel being lined, and is spaced from the vessel wall. Casting composition is then pumped into the space between the consumable form and the vessel wall, and is permitted to harden. Then, another form member is positioned above the first, and casting composition is pumped into the space between the second form member and the vessel wall. This process is repeated, using stacked form members, until the refractory lining is completely installed. <MATH>

IPC 1-7  
**C21B 7/06**

IPC 8 full level  
**B22D 41/02** (2006.01); **C21B 7/06** (2006.01); **F27D 1/16** (2006.01); **F27B 1/14** (2006.01)

CPC (source: EP)  
**B22D 41/023** (2013.01); **C21B 7/06** (2013.01); **F27D 1/1626** (2013.01); **F27B 1/14** (2013.01); **F27D 2001/1631** (2013.01)

Citation (applicant)  
• US 3672649 A 19720627 - ALLEN JOHN E  
• US 5147830 A 19920915 - BANERJEE SUBRATA [US], et al  
• US 3382907 A 19680514 - HOUGH DEAN R  
• DE 2162406 C3 19790301  
• CHEMICAL ABSTRACTS, Columbus, Ohio, US; abstract no. 90248

Cited by  
CN112113430A; EP0921199A1; CN107305100A; CN113260716A

Designated contracting state (EPC)  
AT BE DE ES FR GB IT LU NL SE

DOCDB simple family (publication)  
**EP 0694619 A2 19960131**; **EP 0694619 A3 19960228**; CA 2152683 A1 19960127; CA 2152683 C 19990525

DOCDB simple family (application)  
**EP 95304388 A 19950622**; CA 2152683 A 19950627