

Title (en)
SUPPORT PROP

Title (de)
GRUBENSTEMPEL

Title (fr)
ETANCON

Publication
EP 0695394 B1 19990310 (EN)

Application
EP 94914458 A 19940505

Priority

- GB 9400961 W 19940505
- ZA 933209 A 19930507
- ZA 937954 A 19931026
- ZA 938099 A 19931029
- ZA 94339 A 19940118
- ZA 942942 A 19940429
- ZA 942943 A 19940429
- ZA 942944 A 19940429

Abstract (en)
[origin: WO9427029A1] The support prop consists of an outer tube (12) with an open flared mouth (14) into which a plunger (16) projects. A deforming ring (18) in use engages the plunger and is initially located within the flared mouth of the outer tube. A chamber (26) is provided within the prop into which fluid under pressure can be introduced through an inlet (28) to the chamber to locate the prop between two surfaces by displacing the plunger relative to the outer tube. A seal (24) is located within the chamber to prevent the fluid from escaping between the plunger and the bore of the outer tube.

IPC 1-7
E21D 15/32; **E21D 15/44**

IPC 8 full level
E21D 15/32 (2006.01); **E21D 15/44** (2006.01)

CPC (source: EP US)
E21D 15/32 (2013.01 - EP US); **E21D 15/445** (2013.01 - EP US)

Citation (examination)
ZA 901985 B 19901228 - ANGLO AMER CORP SOUTH AFRICA

Designated contracting state (EPC)
DE GB SE

DOCDB simple family (publication)
WO 9427029 A1 19941124; AU 6682194 A 19941212; AU 674954 B2 19970116; CA 2162369 A1 19941124; CA 2162369 C 20020108; DE 69417023 D1 19990415; DE 69417023 T2 19991118; EP 0695394 A1 19960207; EP 0695394 B1 19990310; RU 2132953 C1 19990710; UA 39955 C2 20010716; US 5720581 A 19980224

DOCDB simple family (application)
GB 9400961 W 19940505; AU 6682194 A 19940505; CA 2162369 A 19940505; DE 69417023 T 19940505; EP 94914458 A 19940505; RU 95122750 A 19940505; UA 95125172 A 19940505; US 54982496 A 19960626