

Title (en)

Process for carburizing carburisable work pieces under the action of plasma-pulses

Title (de)

Verfahren zum Aufkohlen von Bauteilen aus kohlungsfähigen Werkstoffen mittels einer impulsförmig betriebenen Plasma-entladung

Title (fr)

Procédé pour la carburation de pièces carburables par des impulsions à plasma

Publication

EP 0695813 A3 19970212 (DE)

Application

EP 95109082 A 19950613

Priority

DE 4427902 A 19940806

Abstract (en)

[origin: US5558725A] Workpieces of carburizable materials, especially steels, are carburized by means of a pulsed plasma discharge in a carbon-containing atmosphere at pressures of 0.1-30 mbars and at pulsed voltages of 200-2,000 V, preferably of 300-1,000 V. A continuously applied baseline voltage, which is below the breakdown voltage, is superimposed on the pulsed voltage. The baseline voltage is preferably a direct-current voltage, which is in the range of 10-150 V, preferably of 20-100 V.

IPC 1-7

C23C 8/36

IPC 8 full level

C23C 8/36 (2006.01); **C23C 8/38** (2006.01)

CPC (source: EP US)

C23C 8/38 (2013.01 - EP US)

Citation (search report)

- [X] US 2946708 A 19600726 - BERNHARD BERGHAUS, et al
- [XP] FR 2708624 A1 19950210 - NEUVILLE STEPHANE [FR]
- [X] US 4406765 A 19830927 - HIGASHI AKIO [JP], et al
- [A] DE 2842407 A1 19800403 - STAUDER NORBERT
- [A] DE 4003623 A1 19910808 - KLOECKNER IONON [DE]
- [AD] DE 4238993 C1 19930701
- [X] PATENT ABSTRACTS OF JAPAN vol. 14, no. 342 (C - 0743) 24 July 1990 (1990-07-24)

Cited by

EP1143031A3; DE10021583A1; US6776854B2; WO9931291A3

Designated contracting state (EPC)

AT CH DE FR GB IT LI SE

DOCDB simple family (publication)

US 5558725 A 19960924; AT E184329 T1 19990915; DE 4427902 C1 19950330; DE 59506771 D1 19991014; EP 0695813 A2 19960207; EP 0695813 A3 19970212; EP 0695813 B1 19990908; JP H08170162 A 19960702

DOCDB simple family (application)

US 49821695 A 19950705; AT 95109082 T 19950613; DE 4427902 A 19940806; DE 59506771 T 19950613; EP 95109082 A 19950613; JP 19884395 A 19950803