

Title (en)

Method for correcting the dissymmetries of a sensor wheel

Title (de)

Verfahren zur Korrektur der Unsymmetrien eines Geberrades

Title (fr)

Procédé de correction des dissymétries d'une roue de capteur

Publication

**EP 0695865 B1 19981111 (FR)**

Application

**EP 95401816 A 19950802**

Priority

FR 9409646 A 19940803

Abstract (en)

[origin: EP0695865A1] The process for correcting signals received from a sensor (3) detecting the passage of a toothed coding wheel (1) involves defining a value of the measurement parameter for each of the angular sectors (2) of the target wheel (1). This wheel has positions corresponding to the phases of operation of the IC engine. The average is determined for the value corresponding to each angular sector. For each sector, a compensation term is defined in order to correct for lack of symmetry in the toothed wheel. This allows correction of the ignition timing and fuel supply timing.

IPC 1-7

**F02D 41/34**

IPC 8 full level

**F02D 41/34** (2006.01)

CPC (source: EP)

**F02D 41/009** (2013.01)

Cited by

US6125824A; EP1757946A3; FR3035448A1; US10415489B2; US6363912B1; WO9803785A1; WO2016169644A1; WO9940308A1

Designated contracting state (EPC)

DE ES GB IT SE

DOCDB simple family (publication)

**EP 0695865 A1 19960207; EP 0695865 B1 19981111**; DE 69505910 D1 19981217; DE 69505910 T2 19990701; ES 2126848 T3 19990401; FR 2723400 A1 19960209; FR 2723400 B1 19961011

DOCDB simple family (application)

**EP 95401816 A 19950802**; DE 69505910 T 19950802; ES 95401816 T 19950802; FR 9409646 A 19940803