

Title (en)

METHOD OF OPERATING A SPRINKLER INSTALLATION AND A DEVICE FOR EXECUTING THE METHOD

Title (de)

VERFAHREN ZUR BETÄIGUNG VON SPRINKLERANLAGEN UND VORRICHTUNG ZUR DURCHFÜHRUNG DES VERFAHRENS

Title (fr)

PROCEDE D'EXPLOITATION D'UN RESEAU SPRINKLEUR ET DISPOSITIF PREVU A CET EFFET

Publication

EP 0696218 A1 19960214 (EN)

Application

EP 94913247 A 19940425

Priority

- SE 9400366 W 19940425
- SE 9301490 A 19930430

Abstract (en)

[origin: WO9425113A1] A pump device for feeding a sprinkler system comprises a speed controlled, D.C. driven mother pump (1) which continuously maintains a stand-by pressure in the sprinkler system, and at least one slave pump (2) which is switched on when, after alarm has been given, the performance of the mother pump in maintaining the stand-by pressure has reached a predetermined part of its maximum value. The performance of the mother pump is then reduced to a predetermined lower level, and the slave pump or pumps are stopped when no more needed.

IPC 1-7

A62C 35/00; A62C 35/60; A62C 37/36; A62C 37/40

IPC 8 full level

A62C 35/58 (2006.01); **A62C 35/02** (2006.01); **A62C 35/60** (2006.01); **A62C 37/40** (2006.01)

CPC (source: EP)

A62C 35/026 (2013.01); **A62C 35/60** (2013.01); **A62C 37/40** (2013.01); **A62C 99/0072** (2013.01)

Citation (search report)

See references of WO 9425113A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB IT LI NL PT

DOCDB simple family (publication)

WO 9425113 A1 19941110; AU 6547894 A 19941121; EP 0696218 A1 19960214; JP 3335469 B2 20021015; JP H07116281 A 19950509;
SE 501398 C2 19950206; SE 9301490 D0 19930430; SE 9301490 L 19941031; TW 309437 B 19970701

DOCDB simple family (application)

SE 9400366 W 19940425; AU 6547894 A 19940425; EP 94913247 A 19940425; JP 7477594 A 19940413; SE 9301490 A 19930430;
TW 83103414 A 19940418