

Title (en)

Method for starting a dampening unit of an offset printing press

Title (de)

Verfahren zum Anfahren eines Feuchtwerkes einer Offsetdruckmaschine

Title (fr)

Procédé pour démarrer une unité de mouillage d'une machine d'impression offset

Publication

EP 0697283 B1 19980218 (DE)

Application

EP 95110974 A 19950713

Priority

DE 4428887 A 19940818

Abstract (en)

[origin: EP0697283A2] Before the damp applicator roller (3) is placed against the damping roller (1) which supplies the damping medium, the damping roller is driven at such a speed that its circumferential speed coincides with that of the damp applicator roller (3). The speed for driving the damping roller (1) supplying the damping medium is determined from a preselectable basic speed for starting up the offset printing machine. After the input of the command for setting the applicator roller against the damping roller the latter is first accelerated to the proposed speed and then the applicator roller is moved time delayed up to the damping roller.

IPC 1-7

B41F 7/26; **B41F 33/10**

IPC 8 full level

B41F 7/26 (2006.01); **B41F 33/10** (2006.01)

CPC (source: EP)

B41F 7/26 (2013.01); **B41F 33/10** (2013.01)

Designated contracting state (EPC)

AT BE CH DE FR GB LI

DOCDB simple family (publication)

EP 0697283 A2 19960221; **EP 0697283 A3 19961218**; **EP 0697283 B1 19980218**; AT E163278 T1 19980315; DE 4428887 A1 19960222; DE 4428887 C2 19960711; DE 59501462 D1 19980326

DOCDB simple family (application)

EP 95110974 A 19950713; AT 95110974 T 19950713; DE 4428887 A 19940818; DE 59501462 T 19950713