

Title (en)
INSULATION BATT WITH LOW FRICTION FACING

Title (de)
DÄMPFUNGSPLATTE MIT EINER EINE GERINGE REIBUNG AUFWEISENDEN OBERFLÄCHE

Title (fr)
PLAQUE ISOLANTE AYANT UN REVETEMENT A FAIBLE FRICTION

Publication
EP 0701645 B1 19970820 (EN)

Application
EP 93914377 A 19930603

Priority
US 9305328 W 19930603

Abstract (en)
[origin: WO9429540A1] A compressible mineral fiber insulation batt (10) has opposed major surfaces (12) and opposed side surfaces, and a polymeric facing (18) adhered with fastening means (20) to both of the major surfaces (12) to prevent relative movement between the facing (18) and the batt (10), where the facing (18) is less than or equal to 1.02E-5 meters (1 mil) in thickness and the facing (18) is sufficiently low mass as to exhibit a flame spread rating of 25 or less in the adhered condition.

IPC 1-7
E04B 1/76; **E04B 1/78**; **E04C 2/24**

IPC 8 full level
E04B 1/80 (2006.01); **E04B 1/76** (2006.01); **E04B 1/78** (2006.01); **E04C 2/24** (2006.01)

CPC (source: EP)
E04B 1/7662 (2013.01); **E04B 1/78** (2013.01); **E04C 2/246** (2013.01)

Designated contracting state (EPC)
DE ES FR GB IT SE

DOCDB simple family (publication)
WO 9429540 A1 19941222; AU 4406093 A 19950103; DE 69313306 D1 19970925; DE 69313306 T2 19980305; EP 0701645 A1 19960320; EP 0701645 B1 19970820; ES 2105283 T3 19971016; JP H08511070 A 19961119; KR 100189213 B1 19990601; KR 960702879 A 19960523

DOCDB simple family (application)
US 9305328 W 19930603; AU 4406093 A 19930603; DE 69313306 T 19930603; EP 93914377 A 19930603; ES 93914377 T 19930603; JP 50169395 A 19930603; KR 19950705446 A 19951202