

Title (en)  
High pressure discharge lamp

Title (de)  
Hochdruckentladungslampe

Title (fr)  
Lampe à décharge haute pression

Publication  
**EP 0703600 B1 20000126 (DE)**

Application  
**EP 95112861 A 19950816**

Priority  
DE 9415217 U 19940921

Abstract (en)  
[origin: EP0703600A2] The lamp has a discharge vessel (2) contg. an axially mounted cathode (4) and anode (3) and an ionisable filling. The cathode has a cylindrical base body (8) which narrows to a point (10) and the cathode is at least partially coated by a carbide film. The whole of the narrowing region between the tip and the base body is free of carbide, whilst the base body is at least partly coated with carbide. The lamp contains mercury in a quantity of 70 to 130 mg/cm<sup>3</sup>, the electrode separation is 0.4 to 0.8 mm. and the working voltage is about 20 to 29 volts, esp. about 23 volts.

IPC 1-7  
**H01J 61/073**

IPC 8 full level  
**H01J 61/02** (2006.01); **H01J 61/073** (2006.01); **H01J 61/16** (2006.01); **H01J 61/20** (2006.01); **H01J 61/82** (2006.01)

CPC (source: EP US)  
**H01J 61/025** (2013.01 - EP US); **H01J 61/073** (2013.01 - EP US); **H01J 61/0735** (2013.01 - EP US); **H01J 61/16** (2013.01 - EP US); **H01J 61/20** (2013.01 - EP US); **H01J 61/82** (2013.01 - EP US)

Cited by  
DE10137794B4; WO2008116756A1

Designated contracting state (EPC)  
BE DE FR GB IT NL

DOCDB simple family (publication)  
**DE 9415217 U1 19960125**; DE 59507686 D1 20000302; EP 0703600 A2 19960327; EP 0703600 A3 19980506; EP 0703600 B1 20000126; JP 3022910 U 19960402; US 5629585 A 19970513

DOCDB simple family (application)  
**DE 9415217 U 19940921**; DE 59507686 T 19950816; EP 95112861 A 19950816; JP 989095 U 19950920; US 51018595 A 19950802