

Title (en)

RETRACTING TIP TROCAR WITH PLUNGER SENSOR

Title (de)

TROKAR MIT ZURÜCKZIEHBARER SPITZE UND FÜHLER

Title (fr)

TROCART A EMBOUT RETRACTEUR POURVU DE PISTONS DETECTEURS

Publication

EP 0705077 A1 19960410 (EN)

Application

EP 94918161 A 19940527

Priority

- US 9406048 W 19940527
- US 6917993 A 19930528

Abstract (en)

[origin: WO9427513A1] A cannula is extended through the wall of a body cavity by a trocar having a piercing head (42) slidable through the cannula between a condition extending distally from the cannula and a condition retracted within the cannula. A latch (62) releasably secures the piercing head (42) in the extended condition against the force of a spring (60) which normally biases the piercing head (42) to the retracted condition. Resiliently biased plungers (38) extend longitudinally of the piercing head (42) for retraction in response to counterforce as the piercing head (42) advances through the wall of a body passage and extension upon the release of the counterforce. Extension of the plungers (38) upon release of the counterforce functions to release the piercing head (42) for retraction.

IPC 1-7

A61B 17/34

IPC 8 full level

A61B 17/34 (2006.01)

CPC (source: EP US)

A61B 17/3496 (2013.01 - EP US)

Citation (search report)

See references of WO 9427513A1

Cited by

DE102006059012B3; US8057502B2; US8048099B2; EP2100564A1; WO2008071257A1; US8105348B2

Designated contracting state (EPC)

BE DE DK ES FR GB IE IT NL

DOCDB simple family (publication)

WO 9427513 A1 19941208; AU 6960394 A 19941220; DE 69409523 D1 19980514; DE 69409523 T2 19981015; DK 0705077 T3 19990125; EP 0705077 A1 19960410; EP 0705077 B1 19980408; ES 2115951 T3 19980701; US 5527335 A 19960618

DOCDB simple family (application)

US 9406048 W 19940527; AU 6960394 A 19940527; DE 69409523 T 19940527; DK 94918161 T 19940527; EP 94918161 A 19940527; ES 94918161 T 19940527; US 33559794 A 19941108