

Title (en)

Method for generating an ink layer with a thickness oriented to the production job in an inking unit

Title (de)

Verfahren zur Erzeugung einer fordruckgerechten Farbschichtdicke in einem Farbwerk

Title (fr)

Procédé pour la formation d'une couche d'encre d'une épaisseur orientée vers l'impression continue dans une unité d'enrage

Publication

EP 0706885 B1 19970604 (DE)

Application

EP 95114700 A 19950919

Priority

DE 4436953 A 19941015

Abstract (en)

[origin: EP0706885A1] A set amount of ink is distributed over the rollers while running the press with the paper feed shut off. The rollers are separated from the block cylinder, the metering components are opened to the same settings and the lifting roller is put in a set position, until a basic amount of ink is in the inking mechanism. The basic amount of ink to fill the inking mechanism is calculated from the ink required for a particular printing batch, and from the latter an equalising-layer thickness is calculated. The metering components are set dependent on this thickness. The press is then run at these settings until the ink thickness set at the metering components is available evenly at all inking rollers. The basic amount of ink and the equalising-layer thickness can be calculated by computer in accordance with the laws of ink-separation from the ink requirement of the printing surface areas of the printing block.

IPC 1-7

B41F 31/00; B41F 33/00

IPC 8 full level

B41F 31/02 (2006.01); **B41F 31/00** (2006.01); **B41F 31/08** (2006.01); **B41F 31/30** (2006.01); **B41F 33/00** (2006.01)

CPC (source: EP US)

B41F 31/00 (2013.01 - EP US); **B41F 33/0027** (2013.01 - EP US)

Cited by

EP2008815A3; DE102007029341A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0706885 A1 19960417; EP 0706885 B1 19970604; AT E153914 T1 19970615; DE 4436953 C1 19960515; DE 59500288 D1 19970710;
JP 3459321 B2 20031020; JP H08183167 A 19960716; US 5590599 A 19970107

DOCDB simple family (application)

EP 95114700 A 19950919; AT 95114700 T 19950919; DE 4436953 A 19941015; DE 59500288 T 19950919; JP 26581995 A 19951013;
US 54322295 A 19951013