

Title (en)

Tool for finishing joint with permanently elastic sealant

Title (de)

Werkzeug zur Nacharbeit von Fugen aus dauerelastischer Fugenmasse

Title (fr)

Outil pour la finition des joints en jointoyage élastique permanent

Publication

EP 0711887 B1 19960724 (DE)

Application

EP 95105595 A 19950413

Priority

DE 9413523 U 19940823

Abstract (en)

[origin: EP0711887A1] The tool is a flat plate with a constant thickness and a circumferential edge (2) protruding on both sides perpendicular to the plane (1) of the plate. The edge is formed by three adjoining edges of which two (3,4) are straight and the third (5) is curved. The two straight edges and the longer of these two edges and the curved edge together include an acute angle. The curved edge runs in a convex curve. The corner formed by the longer of the two straight edges and by the curved edge is rounded. The distance of the curved edge from the longer straight edge increases constantly towards the shorter straight edge.

IPC 1-7

E04F 21/16

IPC 8 full level

E04F 21/16 (2006.01); **E04F 21/165** (2006.01)

CPC (source: EP)

E04F 21/1652 (2013.01)

Citation (examination)

- DE 8503947 U1 19850502
- DE 8708414 U1 19870813
- Zeitschrift "Selbst ist der Mann: das Heimwerker-Magazin", Nr. 11 vom November 1988, Köln; Deckblatt und Seite 73

Cited by

EP4375453A1; EP1666683A1; JP2009518178A; EP4375452A1; DE10154442A1; DE102004058539A1; EP1976677A4; DE102010045992A1; DE202010012825U1; EP1308579A2; DE202022106549U1; DE202022106552U1

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL

DOCDB simple family (publication)

EP 0711887 A1 19960515; EP 0711887 B1 19960724; EP 0711887 B2 20030716; AT E140749 T1 19960815; DE 59500006 D1 19960829; DE 9413523 U1 19941013

DOCDB simple family (application)

EP 95105595 A 19950413; AT 95105595 T 19950413; DE 59500006 T 19950413; DE 9413523 U 19940823