

Publication

EP 0712725 A3 19960605

Application

EP 95117485 A 19951107

Priority

DE 4440239 A 19941110

Abstract (en)

[origin: EP0712725A2] The roller element finds application in a rotary printing machine during foam plate (15) exchange. It consists of several, individually adjustable rollers (7), arranged along the jacket of the forme cylinder (3). One or several first rollers (7) are adjustable on the forme cylinders during the forme plate mounting, while one or more second rollers are adjustably usable during the forme plate dismounting. Pref. the two types of rollers are fitted to the forme cylinder alternately adjacent to each other.

IPC 1-7

B41F 27/12

IPC 8 full level

B41F 27/12 (2006.01)

CPC (source: EP US)

B41F 27/1206 (2013.01 - EP US)

Citation (search report)

- [PX] EP 0678382 A1 19951025 - HEIDELBERGER DRUCKMASCH AG [DE], et al
- [PXA] EP 0679513 A2 19951102 - HEIDELBERGER DRUCKMASCH AG [DE]
- [A] WO 9406630 A1 19940331 - KOENIG & BAUER AG [DE], et al
- [A] EP 0433798 A2 19910626 - KOENIG & BAUER AG [DE]

Cited by

DE102009004980A1; DE102008019515A1; US6779452B2; US6792860B2; DE10024329A1; DE10238177B3; DE10238179B3; DE102006050568B3; DE102005017182A1; EP1712359A3; EP0739728A3; US5718175A; EP1712359A2; US6345575B1; WO0187614A1; WO0187613A1; EP2110247A2; EP2110246A2; EP1535735A2; US7240616B2; WO2004020205A2; EP1543967A2; US7237484B2; US7237483B2; US7448320B2; US7159512B2; US7546801B2; US7562623B2

Designated contracting state (EPC)

CH DE FR GB IT LI SE

DOCDB simple family (publication)

DE 4440239 A1 19960515; DE 4440239 C2 19990930; DE 4440239 C5 20071122; DE 59505896 D1 19990617; EP 0712725 A2 19960522; EP 0712725 A3 19960605; EP 0712725 B1 19990512; EP 0712725 B2 20040901; JP 2922141 B2 19990719; JP H08207249 A 19960813; US 5617792 A 19970408

DOCDB simple family (application)

DE 4440239 A 19941110; DE 59505896 T 19951107; EP 95117485 A 19951107; JP 28535695 A 19951101; US 55591595 A 19951113