

Title (en)

DEVICE FOR ELECTROMAGNETICALLY SECURING A LOCK BARREL

Title (de)

EINRICHTUNG ZUM ELEKTROMAGNETISCHEN VERRIEGELN EINES SCHLIESSZYLINDERS EINES SCHLOSSES

Title (fr)

DISPOSITIF DE BLOCAGE ELECTROMAGNETIQUE DU BARILLET DE FERMETURE D'UNE SERRURE

Publication

EP 0715674 A1 19960612 (DE)

Application

EP 95923113 A 19950630

Priority

- AT 9500139 W 19950630
- AT 129494 A 19940630

Abstract (en)

[origin: US5699686A] PCT No. PCT/AT95/00139 Sec. 371 Date Feb. 22, 1996 Sec. 102(e) Date Feb. 22, 1996 PCT Filed Jun. 30, 1995 PCT Pub. No. WO96/00830 PCT Pub. Date Jan. 11, 1996The device for electromagnetically blocking the closing cylinder (2) of a lock (1) includes a rotary drive comprising a coil (12) and a rotor (7). Depending on the rotary position of the rotor (7), the movable tumbler (4) may be disengaged from the recess (3) of the locking cylinder. In the blocking position, disengagement is prevented by abutment on the end face (11) of the rotor. (FIG. 1)

IPC 1-7

E05B 47/06

IPC 8 full level

E05B 27/00 (2006.01); **E05B 47/00** (2006.01); **E05B 47/06** (2006.01)

CPC (source: EP US)

E05B 47/063 (2013.01 - EP US); **E05B 47/0005** (2013.01 - EP US); **E05B 47/0012** (2013.01 - EP US); **Y10T 70/7057** (2015.04 - EP US); **Y10T 70/713** (2015.04 - EP US)

Citation (search report)

See references of WO 9600830A1

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

US 5699686 A 19971223; AT 405315 B 19990726; AT A129494 A 19981115; AT E187223 T1 19991215; DE 59507333 D1 20000105; EP 0715674 A1 19960612; EP 0715674 B1 19991201; FI 960903 A0 19960227; FI 960903 A 19960227; JP H09502494 A 19970311; WO 9600830 A1 19960111

DOCDB simple family (application)

US 60097896 A 19960222; AT 129494 A 19940630; AT 9500139 W 19950630; AT 95923113 T 19950630; DE 59507333 T 19950630; EP 95923113 A 19950630; FI 960903 A 19960227; JP 50263896 A 19950630