

Title (en)

PROCESS AND DEVICE FOR INJECTING A SEALING COMPOUND INTO TOE-TYPE TURN-LOCK FASTENERS

Title (de)

VORRICHTUNG UND VERFAHREN ZUM EINBRINGEN VON DICHTUNGSMASSE IN NOCKENDREHVERSCHLÜSSE

Title (fr)

PROCEDE ET DISPOSITIF D'INTRODUCTION D'UN MATERIAU D'ETANCHEITE DANS DES FERMETURES DEMI-TOUR A ERGOTS

Publication

EP 0719208 A1 19960703 (DE)

Application

EP 94925450 A 19940811

Priority

- DE 4329948 A 19930904
- EP 9402678 W 19940811

Abstract (en)

[origin: US5763004A] PCT No. PCT/EP94/02678 Sec. 371 Date Mar. 22, 1996 Sec. 102(e) Date Mar. 22, 1996 PCT Filed Aug. 11, 1994 PCT Pub. No. WO95/07174 PCT Pub. Date Mar. 16, 1995Also disclosed is an appliance for introducing sealing compound into lug caps, the appliance containing a turntable for accommodating the cap, and an injection unit, the injection unit containing a nozzle block, which has annularly arranged injection nozzles, and a delivery device for the sealing compound, the turntable and the nozzle block being arranged so as to be centered and the nozzle block being rotatable in the same direction as the turntable. The invention also relates to a process for introducing sealing compound into lug caps and to the use of the appliance for injecting sealing compound into lug caps.

IPC 1-7

B29C 70/80

IPC 8 full level

B65D 53/06 (2006.01); **C09K 3/10** (2006.01)

CPC (source: EP US)

B65D 53/06 (2013.01 - EP US); **C09K 3/10** (2013.01 - EP US); **B29C 2043/3433** (2013.01 - EP US); **B29C 2043/3444** (2013.01 - EP US); **C09K 2200/0635** (2013.01 - EP US)

Citation (search report)

See references of WO 9507174A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

US 5763004 A 19980609; CA 2170044 A1 19950216; DE 4329948 A1 19950309; EP 0719208 A1 19960703; NO 960827 D0 19960229; NO 960827 L 19960229; WO 9507174 A1 19950316

DOCDB simple family (application)

US 59163396 A 19960322; CA 2170044 A 19940811; DE 4329948 A 19930904; EP 9402678 W 19940811; EP 94925450 A 19940811; NO 960827 A 19960229