

Title (en)

Steam boiler of once-through type and process for operating the same

Title (de)

Durchlaufdampferzeuger und Verfahren zu dessen Betrieb

Title (fr)

Chaudière à vapeur du type à circulation ouverte, et procédé de faire fonctionner une telle chaudière

Publication

EP 0720714 B1 19980325 (DE)

Application

EP 94926796 A 19940919

Priority

- DE 9401086 W 19940919
- DE 4333404 A 19930930

Abstract (en)

[origin: WO9509325A1] In order to avoid the inconvenience that results from a faulty heating of individual pipes (10) of a steam generator (2) with vertical pipes arranged in the combustion chamber, the mass flow density m in the pipes (10) is set below a predetermined maximum value (curve B) which depends on the inner diameter d of the used pipes. In order to avoid inadmissibly high pipe wall temperatures even at the proximity of a critical pressure of about 200 to 221 bars, the inner surface of each pipe (10) is further provided with a surface structure that causes a high turbulence and/or a longitudinal vortex in the flowing medium. The components of the flowing medium are thus intimately mixed so that a good heat transmission is achieved.

IPC 1-7

F22B 37/10; F28F 1/40

IPC 8 full level

F22B 21/02 (2006.01); **F22B 37/10** (2006.01); **F22B 37/12** (2006.01); **F28F 1/40** (2006.01); **F28F 13/02** (2006.01)

CPC (source: EP KR US)

F22B 37/10 (2013.01 - KR); **F22B 37/103** (2013.01 - EP US); **F28F 1/40** (2013.01 - EP KR US); **F28F 13/02** (2013.01 - EP US)

Designated contracting state (EPC)

CH DE FR GB LI

DOCDB simple family (publication)

DE 4333404 A1 19950406; CN 1132548 A 19961002; DE 59405540 D1 19980430; EP 0720714 A1 19960710; EP 0720714 B1 19980325; JP H09503284 A 19970331; KR 960705177 A 19961009; RU 2123634 C1 19981220; US 5706766 A 19980113; WO 9509325 A1 19950406

DOCDB simple family (application)

DE 4333404 A 19930930; CN 94193594 A 19940919; DE 59405540 T 19940919; DE 9401086 W 19940919; EP 94926796 A 19940919; JP 51004795 A 19940919; KR 19960701726 A 19960330; RU 96108253 A 19940919; US 62777996 A 19960401