

Title (en)

METHOD AND APPARATUS FOR SELECTIVELY-ENABLED DIVERSITY SIGNALING IN A RADIO COMMUNICATIONS SYSTEM

Title (de)

VERFAHREN UND ANORDNUNG ZUR SELEKTIV EINGESCHALTETEN DIVERSITYSIGNALISIERUNG IN EINEM  
FUNKKOMMUNIKATIONSSYSTEM

Title (fr)

PROCEDE ET APPAREIL DE SIGNALISATION EN DIVERSITE VALIDEE SELECTIVEMENT DANS UN SYSTEME DE  
RADIOCOMMUNICATIONS

Publication

**EP 0720792 B1 19991124 (EN)**

Application

**EP 94923925 A 19940711**

Priority

- US 9407670 W 19940711
- US 11452693 A 19930831

Abstract (en)

[origin: US5345600A] In a radio communications system, a selectively enabled time- and/or frequency-diverse signaling scheme is employed to improve signal quality. In particular, a method of exchanging a message between communication devices using a communications resource might include the step of transmitting a first portion of the message on a first frequency within the communications resource. After determining the quality of the communications resource to be unfavorable, a second portion of the message might be transmitted on the first frequency, and also re-transmitted on a second frequency and/or at a separate time.

IPC 1-7

**H04B 1/10**; **H04B 7/06**; **H04B 7/12**

IPC 8 full level

**H04B 7/02** (2018.01); **H04B 7/12** (2006.01); **H04L 1/00** (2006.01); **H04L 1/18** (2006.01); **H04L 1/20** (2006.01)

CPC (source: EP US)

**H04B 7/02** (2013.01 - EP); **H04B 7/12** (2013.01 - EP US); **H04L 1/0001** (2013.01 - EP US); **H04L 1/04** (2013.01 - EP US);  
**H04L 1/0026** (2013.01 - EP US)

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

**US 5345600 A 19940906**; CN 1043597 C 19990609; CN 1128590 A 19960807; DE 69421822 D1 19991230; DE 69421822 T2 20000615;  
EP 0720792 A1 19960710; EP 0720792 A4 19980311; EP 0720792 B1 19991124; JP H09502065 A 19970225; WO 9506981 A1 19950309

DOCDB simple family (application)

**US 11452693 A 19930831**; CN 94193018 A 19940711; DE 69421822 T 19940711; EP 94923925 A 19940711; JP 50809994 A 19940711;  
US 9407670 W 19940711