

Title (en)

Fluid-pressure actuator with a magnetic field sensor

Title (de)

Druckmittelbetätigte Zylinder-Kolben-Anordnung mit einem Magnetfeldsensor

Title (fr)

Vérin d'actionnement à fluide à capteur de champs magnétique

Publication

EP 0721067 B1 20020828 (DE)

Application

EP 95120518 A 19951223

Priority

DE 19500137 A 19950104

Abstract (en)

[origin: EP0721067A2] The piston-cylinder device has an annular permanent magnet (3) attached to the piston (11), cooperating with a magnetic field sensor (2) within the cylinder (10), for detecting the piston position. The permanent magnet is magnetised in the axial direction of the piston-cylinder device and provided by ferromagnetic discs (32,33) for guiding the magnetic flux. The piston has an open groove (31) receiving the permanent magnet, which has an outer dia. only slightly less than the inner dia. of the cylinder, which has a recess receiving a sleeve (21) of a non-magnetic material, incorporating the magnetic field sensor.

IPC 1-7

F15B 15/28

IPC 8 full level

F15B 15/28 (2006.01)

CPC (source: EP)

F15B 15/2807 (2013.01)

Cited by

CN109312856A; EP1445494A3; CN102943784A; EP2878831A1; DE102005030722A1; CN109162996A; US8365651B2; WO2017211519A1; WO2004081388A1

Designated contracting state (EPC)

AT DE DK ES FR GB IE IT NL SE

DOCDB simple family (publication)

EP 0721067 A2 19960710; EP 0721067 A3 19980211; EP 0721067 B1 20020828; AT E223002 T1 20020915; DE 19500137 A1 19960711; DE 59510348 D1 20021002

DOCDB simple family (application)

EP 95120518 A 19951223; AT 95120518 T 19951223; DE 19500137 A 19950104; DE 59510348 T 19951223