

Title (en)
Output apparatus

Title (de)
Ausgangsgerät

Title (fr)
Appareil de sortie

Publication
EP 0721172 A2 19960710 (EN)

Application
EP 96200681 A 19900604

Priority

- EP 90306048 A 19900604
- JP 14111389 A 19890605
- JP 14237089 A 19890605

Abstract (en)

There is provided an output apparatus in which an output resolution can be changed and a memory medium including character information of printing dot patterns is detachable. The memory medium has holding means for storing and holding output density information of dot patterns of characters stored in the memory medium. The apparatus comprises: reading means for reading out the output density information from the memory medium; and changing means for changing the output resolution on the basis of the output density which was read out by the reading means. When the output density information which was read out by the reading means differs from the printing resolution of the apparatus itself in the reading mode, the character information of the dot pattern in the memory medium is not used. With the apparatus, even if the number of dots constructing a character was changed, the character pattern can be automatically output at the optimum output resolution. <IMAGE>

IPC 1-7
G06K 15/02

IPC 8 full level
G06K 15/02 (2006.01)

CPC (source: EP US)
G06K 15/02 (2013.01 - EP US); **G06K 2215/0025** (2013.01 - EP US); **G06K 2215/0037** (2013.01 - EP US)

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0402074 A2 19901212; EP 0402074 A3 19920115; EP 0402074 B1 19961030; DE 69029009 D1 19961205; DE 69029009 T2 19970306;
EP 0721172 A2 19960710; EP 0721172 A3 19970924; US 5502794 A 19960326; US 5909538 A 19990601

DOCDB simple family (application)
EP 90306048 A 19900604; DE 69029009 T 19900604; EP 96200681 A 19900604; US 24740394 A 19940523; US 58291296 A 19960104