

Title (en)

Process for damp-proofing masonry

Title (de)

Verfahren zum Sanieren von feuchtem Mauerwerk

Title (fr)

Procédé d'assainissement d'un ouvrage de maçonnerie humide

Publication

**EP 0721536 B1 19990210 (DE)**

Application

**EP 94926081 A 19940902**

Priority

- DE 9401021 W 19940902
- DE 4332272 A 19930923

Abstract (en)

[origin: WO9508679A1] In order to damp-proof damp masonry (12) with the aid of paraffin injections acting as a damp course, it is proposed that a heated tank acting on the underpressure principle as a container for the liquid paraffin (2). It is thus possible to prevent further liquid paraffin (2) from escaping from the blind holes (11) made in the masonry (12) for injection purposes. Prior drying of the masonry (12) can also be obviated by the simultaneous heating of the paraffin (2) in the blind hole (11).

IPC 1-7

**E04B 1/64**

IPC 8 full level

**E04B 1/70** (2006.01); **E04B 1/64** (2006.01)

CPC (source: EP)

**E04B 1/648** (2013.01)

Designated contracting state (EPC)

AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**WO 9508679 A1 19950330**; AT E176698 T1 19990215; CZ 286175 B6 20000216; CZ 82796 A3 19960911; DE 4332272 A1 19950330; DE 4332272 C2 19980226; DE 59407814 D1 19990325; DK 0721536 T3 19990920; EP 0721536 A1 19960717; EP 0721536 B1 19990210; ES 2129667 T3 19990616; GR 3029974 T3 19990730; HU 214562 B 19980428; HU 9600705 D0 19960528; HU T74284 A 19961128; PL 175909 B1 19990331; PL 313614 A1 19960708; RU 2109885 C1 19980427

DOCDB simple family (application)

**DE 9401021 W 19940902**; AT 94926081 T 19940902; CZ 82796 A 19940902; DE 4332272 A 19930923; DE 59407814 T 19940902; DK 94926081 T 19940902; EP 94926081 A 19940902; ES 94926081 T 19940902; GR 990401053 T 19990416; HU 9600705 A 19940902; PL 31361494 A 19940902; RU 96107791 A 19940902